

屋内照明器具特性

品番 (品名)	L G W 4 5 9 3 4 A	
光源	LDA3L-E17/C/W x1	280.0 l m
管理番号	K0164342(0)DR1	
BZ分類	BZ10	

器具効率	82%	天井	80%				70%				50%				30%				0%	
	上方光束		52%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	30%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	34	24	18	13	31	22	16	12	24	17	12	9	17	12	9	6	1
	中	0.6	0.6	41	31	24	19	37	28	22	17	28	22	17	13	21	16	12	9	3
	否	0.56	1.0	46	36	29	24	41	33	26	22	32	25	21	17	23	19	15	12	5
下方投影面積	等価発光面積	cm ²	1.25	50	41	34	29	45	37	31	26	35	29	24	21	26	21	18	15	6
			1.5	54	45	38	33	48	41	35	30	37	32	27	24	28	24	20	17	8
取付高さ	器具間隔最大限		2.0	58	51	45	39	52	46	40	36	41	36	32	28	31	27	24	21	10
	横方向 (A)	縦方向 (B)	2.5	61	54	49	44	55	49	44	40	43	39	35	32	33	29	27	24	12
H _m	H _m	H _m	3.0	63	57	52	48	57	52	47	43	45	41	38	35	34	31	29	26	13
			4.0	66	61	57	53	60	55	51	48	48	44	41	39	36	34	32	30	16
			5.0	68	64	60	56	61	58	54	51	49	46	44	41	38	36	34	32	17
			7.0	70	67	64	61	64	61	58	55	51	49	47	45	40	38	36	35	20
			10.0	72	69	67	65	65	63	61	59	53	51	50	48	41	40	39	37	22

