

屋内照明器具特性

品番 (品名)	L G W 8 0 2 6 3				
光源	LED2700_70_263 x1 263.0 l m				
管理番号	K0160972 (0) DB 1				
B Z 分類	B Z 8 / 0 . 7 / B Z 7 / 0 . 9 / B Z 6 / 4 . 5 / B Z 5				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	6 %	室指数																	照明率 (X 0 . 0 1)																	Z C M																
下方光束	94 %																																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	48	34	25	19	46	33	24	18	43	31	24	18	40	30	23	18	15																														
		0.6	0.8	58	45	36	29	56	44	35	29	52	42	34	28	49	40	33	27	24																																
		1.0	1.0	66	53	44	37	63	52	43	37	59	49	42	36	55	47	40	35	32																																
		0.56	1.25	72	61	52	45	70	59	51	45	66	57	49	44	62	54	48	43	39																																
下方投影面積	c m ²	1.5	77	67	59	52	75	65	58	51	71	62	56	50	66	59	54	49	45																																	
		2.0	84	75	68	62	82	73	67	61	77	70	64	59	73	67	62	58	54																																	
取付高さ	器具間隔最大限		2.5	88	81	74	69	86	79	73	68	81	75	70	66	77	72	68	64	60																																
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	89	83	77	73	84	79	75	71	80	76	72	69	65																																
H m	0.00 H m	0.00 H m	4.0	95	89	85	80	93	88	83	79	88	84	80	77	84	81	78	75	71																																
			5.0	97	93	88	85	95	91	87	83	91	87	84	81	87	84	81	79	74																																
			7.0	100	96	93	90	98	94	92	89	94	91	88	86	90	88	86	84	79																																
			10.0	102	99	97	95	100	97	95	93	96	94	92	90	92	90	89	87	83																																

