

屋内照明器具特性	
品番 (品名)	NTS62811S+NTS90151
光源	LED4000_70_710 x1 710.0 lm
管理番号	K0156488 (1) DJ 1
BZ分類	BZ1

器具効率		1 0 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		1 0 2 %																						
保守率		良	0 . 6 7	0 . 6	1 0 2	1 0 0	9 8	9 7	1 0 2	1 0 0	9 8	9 7	1 0 1	9 9	9 8	9 7	1 0 1	9 9	9 8	9 7	9 6			
		中	0 . 6 3	0 . 8	1 0 4	1 0 2	1 0 0	9 9	1 0 4	1 0 1	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 9	1 0 2	1 0 0	9 9	9 8	9 8			
		否	0 . 5 6	1 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 3	1 0 1	1 0 0	9 9	9 9			
下方投影面積 等価発光面積		c m ²	c m ²	1 . 2 5	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	9 9			
				1 . 5	1 0 7	1 0 5	1 0 4	1 0 3	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0			
				2 . 0	1 0 8	1 0 6	1 0 5	1 0 4	1 0 7	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 0			
取付 高さ	器具間隔最大限		2 . 5	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 1				
	横方向 (A)	縦方向 (B)	3 . 0	1 0 9	1 0 7	1 0 6	1 0 6	1 0 8	1 0 7	1 0 6	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 1				
H m	0 . 2 5 H m	0 . 2 5 H m	4 . 0	1 0 9	1 0 8	1 0 7	1 0 7	1 0 8	1 0 7	1 0 6	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 1					
			5 . 0	1 0 9	1 0 9	1 0 8	1 0 7	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 1				
			7 . 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 9	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 1				
			1 0 . 0	1 1 0	1 1 0	1 0 9	1 0 9	1 0 9	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 1					

