

# 屋内照明器具特性

品番 (品名)	XLW4 2 2 UENZ									
光源	LED5000_85_2320 x1 2320.0 1m									
管理番号	K0143337 (1) DB 1									
BZ分類	BZ5 / 1.4 / BZ4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否	0.81	0.6	57	45	37	32	56	44	37	32	53	43	36	31	51	42	36	31	29
		0.77	0.8	67	56	48	42	66	55	48	42	63	54	47	42	61	52	46	42	40
			1.0	74	63	56	50	72	63	55	50	70	61	55	50	67	59	54	49	47
		0.68	1.25	80	71	63	58	78	70	63	58	75	68	62	57	73	66	61	57	54
下方投影面積	c m <sup>2</sup>	1.5	84	76	69	64	83	75	68	63	80	73	67	63	77	71	66	62	60	
		2.0	90	83	77	72	88	82	76	72	85	80	75	71	83	78	74	70	68	
取付高さ	器具間隔最大限		2.5	93	87	82	78	92	86	82	77	89	84	80	76	86	82	79	76	73
	横方向 (A)	縦方向 (B)	3.0	96	91	86	82	94	90	85	82	91	87	84	81	89	85	82	79	77
1.5m	2.04 m	2.16 m	4.0	99	95	91	88	97	94	90	87	95	91	89	86	92	89	87	85	82
2	2.69	2.71	5.0	101	97	94	92	99	96	93	91	97	94	92	89	94	92	90	88	85
2.5	3.35	3.29	7.0	103	100	98	96	102	99	97	95	99	97	95	93	96	95	93	92	89
3	4	3.88	10.0	105	103	101	99	103	102	100	98	101	99	98	97	98	97	96	95	92

