

屋内照明器具特性

品番 (品名)	LGB15312K														
光源	LDG11L-G/95/W x1 1370.0 lm														
管理番号	K0147988(0)DB1														
BZ分類	BZ6														

器具効率	70%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	4%	室指数	照明率 (X0.01)																ZCM	
下方光束	66%																			
保守率	良 中 否	0.67	0.6	3.6	2.6	2.1	1.6	3.5	2.6	2.0	1.6	3.2	2.5	2.0	1.6	3.0	2.4	1.9	1.6	1.4
		0.63	0.8	4.3	3.4	2.7	2.3	4.1	3.3	2.7	2.3	3.8	3.1	2.6	2.2	3.6	3.0	2.5	2.2	2.0
		0.56	1.0	4.7	3.9	3.2	2.8	4.6	3.8	3.2	2.7	4.3	3.6	3.1	2.7	4.0	3.4	3.0	2.6	2.4
			1.25	5.1	4.3	3.7	3.3	5.0	4.2	3.7	3.2	4.7	4.0	3.6	3.2	4.4	3.9	3.4	3.1	2.8
下方投影面積	c m ²	1.5	5.4	4.7	4.1	3.7	5.3	4.6	4.1	3.6	5.0	4.4	3.9	3.5	4.7	4.2	3.8	3.4	3.2	
		2.0	5.9	5.2	4.7	4.3	5.7	5.1	4.6	4.2	5.4	4.9	4.5	4.1	5.1	4.6	4.3	4.0	3.7	
取付高さ	器具間隔最大限		2.5	6.1	5.6	5.1	4.7	6.0	5.4	5.0	4.6	5.6	5.2	4.8	4.5	5.3	5.0	4.6	4.4	4.1
	横方向 (A)	縦方向 (B)	3.0	6.3	5.8	5.4	5.0	6.2	5.7	5.3	4.9	5.8	5.4	5.1	4.8	5.5	5.2	4.9	4.7	4.4
H m	1.45 H m	1.45 H m	4.0	6.6	6.2	5.8	5.5	6.4	6.0	5.7	5.4	6.1	5.8	5.5	5.2	5.8	5.5	5.3	5.1	4.7
			5.0	6.7	6.4	6.1	5.8	6.6	6.2	6.0	5.7	6.3	6.0	5.7	5.5	6.0	5.7	5.5	5.3	5.0
			7.0	6.9	6.6	6.4	6.2	6.8	6.5	6.3	6.1	6.5	6.2	6.0	5.9	6.2	6.0	5.8	5.7	5.3
			10.0	7.1	6.9	6.7	6.5	6.9	6.7	6.5	6.4	6.6	6.5	6.3	6.2	6.3	6.2	6.1	6.0	5.6

