

|          |                                  |
|----------|----------------------------------|
| 屋内照明器具特性 |                                  |
| 品番 (品名)  | LGB15003Z                        |
| 光源       | LDA4L-H-E17/E/S/W/2 ×1 440.0 l m |
| 管理番号     | K0122381(0)DB1                   |
| BZ分類     | BZ5                              |

|        |                            |          |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|----------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 91%                        | 天井       | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                            | 壁        | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 5%                         | 床        | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 86%                        | 室指数      | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良 0.67<br>中 0.63<br>否 0.56 | 0.6      | 50            | 39 | 32 | 27 | 49  | 38 | 31 | 27 | 46  | 37 | 31 | 26 | 43  | 35 | 30 | 26 | 24  |    |
|        |                            | 0.8      | 59            | 49 | 42 | 36 | 58  | 48 | 41 | 36 | 54  | 46 | 40 | 35 | 52  | 44 | 39 | 35 | 32  |    |
|        |                            | 1.0      | 65            | 56 | 49 | 43 | 64  | 55 | 48 | 43 | 60  | 53 | 47 | 42 | 57  | 51 | 45 | 41 | 39  |    |
|        |                            | 1.25     | 71            | 62 | 56 | 50 | 69  | 61 | 55 | 50 | 66  | 59 | 53 | 49 | 63  | 57 | 52 | 48 | 45  |    |
| 下方投影面積 | c m <sup>2</sup>           | 1.5      | 75            | 67 | 61 | 56 | 73  | 66 | 60 | 55 | 70  | 63 | 58 | 54 | 66  | 61 | 57 | 53 | 50  |    |
|        |                            | 2.0      | 80            | 74 | 68 | 64 | 78  | 72 | 67 | 63 | 75  | 70 | 65 | 62 | 71  | 67 | 63 | 60 | 57  |    |
| 取付高さ   | 器具間隔最大限                    |          | 2.5           | 83 | 78 | 73 | 69  | 82 | 76 | 72 | 68  | 78 | 74 | 70 | 67  | 75 | 71 | 68 | 65  | 62 |
|        | 横方向 (A)                    | 縦方向 (B)  | 3.0           | 86 | 81 | 77 | 73  | 84 | 79 | 76 | 72  | 80 | 77 | 73 | 70  | 77 | 74 | 71 | 69  | 65 |
| H m    | 1.32 H m                   | 1.32 H m | 4.0           | 89 | 85 | 81 | 78  | 87 | 83 | 80 | 77  | 83 | 80 | 78 | 75  | 80 | 77 | 75 | 73  | 70 |
|        |                            |          | 5.0           | 90 | 87 | 84 | 82  | 88 | 86 | 83 | 80  | 85 | 83 | 80 | 78  | 82 | 80 | 78 | 76  | 72 |
|        |                            |          | 7.0           | 92 | 90 | 88 | 86  | 90 | 88 | 86 | 84  | 87 | 85 | 84 | 82  | 84 | 82 | 81 | 80  | 76 |
|        |                            |          | 10.0          | 94 | 92 | 90 | 89  | 92 | 90 | 89 | 87  | 89 | 87 | 86 | 85  | 85 | 84 | 83 | 82  | 78 |

