

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | LGB57629W         |  |          |  |  |
| 光源      | LED3500_70_465 x6 |  | 465.0 lm |  |  |
| 管理番号    | K0161568(0)DB1    |  |          |  |  |
| BZ分類    | BZ8/0.7/BZ7       |  |          |  |  |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |         | 壁               | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 37%     | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 63%     | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.63            | 0.6           | 4.6 | 3.4 | 2.6 | 2.0 | 4.3 | 3.2 | 2.4 | 1.9 | 3.7 | 2.8 | 2.1 | 1.7 | 3.2 | 2.4 | 1.9 | 1.5 | 1.0 |
|        | 中       | 0.6             | 0.8           | 5.5 | 4.3 | 3.4 | 2.8 | 5.1 | 4.0 | 3.2 | 2.6 | 4.4 | 3.5 | 2.8 | 2.4 | 3.7 | 3.0 | 2.5 | 2.1 | 1.5 |
|        | 否       | 0.56            | 1.0           | 6.1 | 4.9 | 4.0 | 3.4 | 5.7 | 4.6 | 3.8 | 3.2 | 4.9 | 4.0 | 3.4 | 2.9 | 4.2 | 3.5 | 2.9 | 2.5 | 1.9 |
|        |         |                 | 1.25          | 6.7 | 5.5 | 4.7 | 4.1 | 6.2 | 5.2 | 4.4 | 3.8 | 5.4 | 4.6 | 3.9 | 3.4 | 4.6 | 3.9 | 3.4 | 3.0 | 2.3 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 7.1 | 6.0 | 5.2 | 4.6 | 6.6 | 5.7 | 4.9 | 4.3 | 5.7 | 5.0 | 4.4 | 3.9 | 4.9 | 4.3 | 3.8 | 3.4 | 2.6 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 7.6 | 6.7 | 6.0 | 5.4 | 7.1 | 6.3 | 5.7 | 5.1 | 6.2 | 5.6 | 5.0 | 4.5 | 5.3 | 4.8 | 4.4 | 4.0 | 3.1 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 8.0 | 7.2 | 6.5 | 6.0 | 7.5 | 6.8 | 6.2 | 5.6 | 6.5 | 6.0 | 5.5 | 5.0 | 5.6 | 5.2 | 4.8 | 4.4 | 3.5 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 8.3 | 7.6 | 6.9 | 6.4 | 7.8 | 7.1 | 6.6 | 6.1 | 6.8 | 6.3 | 5.8 | 5.4 | 5.9 | 5.5 | 5.1 | 4.8 | 3.8 |
| Hm     | 1.48Hm  | 1.48Hm          | 4.0           | 8.6 | 8.0 | 7.5 | 7.0 | 8.1 | 7.6 | 7.1 | 6.7 | 7.1 | 6.7 | 6.3 | 6.0 | 6.2 | 5.9 | 5.6 | 5.3 | 4.2 |
|        |         |                 | 5.0           | 8.9 | 8.4 | 7.9 | 7.5 | 8.3 | 7.9 | 7.5 | 7.1 | 7.3 | 7.0 | 6.6 | 6.3 | 6.4 | 6.1 | 5.9 | 5.6 | 4.5 |
|        |         |                 | 7.0           | 9.1 | 8.7 | 8.4 | 8.0 | 8.6 | 8.3 | 7.9 | 7.6 | 7.6 | 7.3 | 7.1 | 6.8 | 6.7 | 6.4 | 6.2 | 6.0 | 4.8 |
|        |         |                 | 10.0          | 9.3 | 9.1 | 8.8 | 8.5 | 8.8 | 8.6 | 8.3 | 8.1 | 7.8 | 7.6 | 7.4 | 7.2 | 6.9 | 6.7 | 6.5 | 6.4 | 5.2 |

