

# 屋内照明器具特性

|         |                             |  |  |  |  |
|---------|-----------------------------|--|--|--|--|
| 品番 (品名) | LGB51568B                   |  |  |  |  |
| 光源      | LED2700_70_460 x1 460.0 l m |  |  |  |  |
| 管理番号    | K0161574(0)DB1              |  |  |  |  |
| BZ分類    | BZ8/0.7/BZ7                 |  |  |  |  |

|        |                   |          |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|--------|-------------------|----------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 器具効率   | 101%              | 天井       | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |    |
|        | 上方光束              |          | 38%              | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0% |
|        | 下方光束              |          | 63%              |      | 床    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |          |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 保守率    | 良                 | 0.63     | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 中                 | 0.6      | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 否                 | 0.56     | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
|        | 0.56              | 0.56     | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
| 下方投影面積 | c m <sup>2</sup>  |          | 1.25             | 67   | 56   | 47   | 40   | 62   | 52   | 44   | 38   | 54   | 45   | 39   | 34   | 46   | 39   | 34   | 30   | 22   |    |
|        | 等価発光面積            |          | c m <sup>2</sup> | 1.5  | 71   | 60   | 52   | 46   | 66   | 57   | 49   | 43   | 57   | 49   | 43   | 38   | 49   | 43   | 38   | 33   | 25 |
| 取付高さ   | 器具間隔最大限           |          | 2.5              | 81   | 72   | 65   | 59   | 75   | 68   | 62   | 56   | 65   | 59   | 54   | 50   | 56   | 52   | 47   | 44   | 34   |    |
|        | 横方向 (A)           | 縦方向 (B)  | 3.0              | 83   | 76   | 70   | 64   | 78   | 71   | 66   | 61   | 68   | 63   | 58   | 54   | 58   | 54   | 51   | 47   | 37   |    |
| H m    | 1.49 H m          | 1.49 H m | 4.0              | 87   | 81   | 75   | 70   | 82   | 76   | 71   | 67   | 71   | 67   | 63   | 59   | 62   | 58   | 55   | 52   | 41   |    |
|        |                   |          | 5.0              | 89   | 84   | 79   | 75   | 84   | 79   | 75   | 71   | 74   | 70   | 66   | 63   | 64   | 61   | 58   | 55   | 44   |    |
|        |                   |          | 7.0              | 92   | 88   | 84   | 80   | 87   | 83   | 79   | 76   | 76   | 73   | 70   | 68   | 67   | 64   | 62   | 60   | 47   |    |
|        |                   |          | 10.0             | 94   | 91   | 88   | 85   | 89   | 86   | 83   | 81   | 79   | 76   | 74   | 72   | 69   | 67   | 65   | 63   | 51   |    |

