

# 屋内照明器具特性

|         |                        |           |
|---------|------------------------|-----------|
| 品番 (品名) | LGB16078Z              |           |
| 光源      | LDA4L-H-E17/E/S/W/2 ×1 | 440.0 l m |
| 管理番号    | K0123325(0)DB1         |           |
| BZ分類    | BZ3                    |           |

|        |                  |          |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |     |
|--------|------------------|----------|------------------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率   | 73%              | 天井       | 80%              |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |     |
|        | 上方光束             |          | 0%               | 壁    | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束             |          | 73%              |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 )    |          |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    | ZCM |
| 保守率    | 良                | 0.67     | 0.6              | 45   | 37 | 32  | 28  | 44 | 37 | 32  | 28  | 43 | 36 | 32  | 28  | 41 | 35 | 31  | 28 | 27 |     |
|        | 中                | 0.63     | 0.8              | 53   | 46 | 41  | 37  | 52 | 45 | 41  | 37  | 50 | 44 | 40  | 37  | 49 | 43 | 40  | 37 | 35 |     |
|        | 否                | 0.56     | 1.0              | 58   | 51 | 47  | 43  | 57 | 51 | 46  | 43  | 55 | 50 | 46  | 43  | 53 | 49 | 45  | 42 | 41 |     |
|        |                  |          |                  | 1.25 | 62 | 56  | 52  | 48 | 61 | 55  | 51  | 48 | 59 | 54  | 51  | 48 | 57 | 53  | 50 | 47 | 46  |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 64   | 59 | 55  | 52  | 63 | 59 | 55  | 52  | 61 | 57 | 54  | 51  | 60 | 56 | 53  | 51 | 49 |     |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0  | 68 | 64  | 60  | 57 | 67 | 63  | 60  | 57 | 65 | 62  | 59  | 56 | 63 | 60  | 58 | 56 | 54  |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 70   | 67 | 63  | 61  | 69 | 66 | 63  | 60  | 67 | 64 | 62  | 60  | 65 | 63 | 61  | 59 | 57 |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 72   | 68 | 66  | 63  | 71 | 68 | 65  | 63  | 69 | 66 | 64  | 62  | 67 | 65 | 63  | 61 | 60 |     |
| H m    | 1.36 H m         | 1.36 H m | 4.0              | 73   | 71 | 69  | 67  | 72 | 70 | 68  | 66  | 71 | 69 | 67  | 65  | 69 | 67 | 66  | 64 | 63 |     |
|        |                  |          | 5.0              | 74   | 72 | 71  | 69  | 74 | 72 | 70  | 68  | 72 | 70 | 69  | 67  | 70 | 69 | 67  | 66 | 64 |     |
|        |                  |          | 7.0              | 76   | 74 | 73  | 72  | 75 | 73 | 72  | 71  | 73 | 72 | 71  | 70  | 71 | 70 | 69  | 69 | 67 |     |
|        |                  |          | 10.0             | 77   | 76 | 75  | 74  | 76 | 75 | 74  | 73  | 74 | 73 | 72  | 72  | 72 | 72 | 71  | 70 | 68 |     |

