

屋内照明器具特性

品番 (品名)	L G W 4 5 8 1 0 Z															
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1 m															
管理番号	K0126468(0)DB1															
BZ分類	BZ10															

器具効率	67%	天井	80%				70%				50%				30%				0%							
	上方光束		50%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%					
	下方光束		17%		床	10%				10%				10%				10%				0%				
室指数	照明率 (X0.01) ZCM																									
保守率	良	0.63	0.6	0.56	0.6	2.8	2.0	1.5	1.2	2.5	1.8	1.3	1.0	1.8	1.3	1.0	0.7	1.2	0.9	0.6	0.5	0				
	中	0.6	0.6	0.6	0.6	3.3	2.5	2.0	1.6	2.9	2.2	1.8	1.4	2.1	1.7	1.3	1.0	1.4	1.1	0.9	0.7	1				
	否	0.56	0.56	0.56	0.56	3.7	2.9	2.4	2.0	3.2	2.6	2.1	1.8	2.4	1.9	1.6	1.3	1.6	1.3	1.0	0.8	1				
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	2.5	4.0	3.3	2.8	2.4	3.5	2.9	2.5	2.1	2.6	2.2	1.8	1.6	1.8	1.5	1.2	1.0	2				
		2.5	3.0	4.0	5.0	4.9	4.4	3.9	3.6	4.3	3.9	3.5	3.2	3.2	2.9	2.6	2.4	2.2	2.0	1.8	1.6	5				
		3.0	4.0	5.0	6.0	5.0	4.6	4.2	3.8	4.5	4.1	3.7	3.4	3.4	3.1	2.8	2.6	2.3	2.1	2.0	1.8	6				
取付高さ	器具間隔最大限		H m	0.00H m	0.00H m	4.0	5.0	6.0	7.0	5.3	4.9	4.5	4.2	4.7	4.3	4.0	3.8	3.5	3.3	3.1	2.9	2.5	2.3	2.2	2.0	7
	5.0	6.0				7.0	8.0	5.4	5.1	4.8	4.5	4.8	4.5	4.3	4.0	3.7	3.5	3.3	3.1	2.6	2.4	2.3	2.2	8		
	7.0	8.0				9.0	10.0	5.6	5.3	5.1	4.9	5.0	4.7	4.5	4.3	3.8	3.6	3.5	3.3	2.7	2.6	2.5	2.4	10		
						10.0	11.0	12.0	13.0	5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.6	3.9	3.8	3.7	3.6	2.8	2.7	2.6	2.6	11

