

屋内照明器具特性

品番 (品名)	LGB16078Z										
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1 m										
管理番号	K0123325(0)DB1										
BZ分類	BZ3										

器具効率	73%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	0%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	73%																																																			
保守率	良 中 否	0.67	0.6	45	37	32	28	44	37	32	28	43	36	32	28	41	35	31	28	27																																
		0.63	0.8	53	46	41	37	52	45	41	37	50	44	40	37	49	43	40	37	35																																
			1.0	58	51	47	43	57	51	46	43	55	50	46	43	53	49	45	42	41																																
		0.56	1.25	62	56	52	48	61	55	51	48	59	54	51	48	57	53	50	47	46																																
下方投影面積	c m ²	1.5	64	59	55	52	63	59	55	52	61	57	54	51	60	56	53	51	49																																	
		2.0	68	64	60	57	67	63	60	57	65	62	59	56	63	60	58	56	54																																	
取付高さ	器具間隔最大限		2.5	70	67	63	61	69	66	63	60	67	64	62	60	65	63	61	59	57																																
	横方向 (A)	縦方向 (B)	3.0	72	68	66	63	71	68	65	63	69	66	64	62	67	65	63	61	60																																
H m	1.36 H m	1.36 H m	4.0	73	71	69	67	72	70	68	66	71	69	67	65	69	67	66	64	63																																
			5.0	74	72	71	69	74	72	70	68	72	70	69	67	70	69	67	66	64																																
			7.0	76	74	73	72	75	73	72	71	73	72	71	70	71	70	69	69	67																																
			10.0	77	76	75	74	76	75	74	73	74	73	72	72	72	71	70	68	68																																

