

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 0 4 B Z
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0160307 (0) DR 1
B Z 分類	BZ9

器具効率	50 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	25 %		床	10 %				10 %				10 %				10 %				0 %	
下方光束	25 %		室指数	照明率 (X0.01)																Z C M	
保守率	良 0.63	0.6 中 否 0.56	0.6	2.2	1.6	1.2	0.9	2.0	1.4	1.1	0.8	1.6	1.2	0.9	0.7	1.3	0.9	0.7	0.5	0.3	
	0.8		2.6	2.0	1.5	1.2	2.4	1.8	1.4	1.1	1.9	1.5	1.2	1.0	1.5	1.2	1.0	0.8	0.4		
	1.0		2.9	2.3	1.9	1.5	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.2	1.7	1.4	1.1	1.0	0.6		
	1.25		3.2	2.6	2.2	1.8	2.9	2.4	2.0	1.7	2.4	2.0	1.7	1.4	1.9	1.6	1.4	1.2	0.7		
下方投影面積	cm ²	等価発光面積	cm ²	1.5	3.4	2.8	2.4	2.1	3.1	2.6	2.2	1.9	2.5	2.2	1.9	1.6	2.0	1.7	1.5	1.3	0.8
				2.0	3.6	3.2	2.8	2.5	3.3	2.9	2.6	2.3	2.8	2.4	2.2	1.9	2.2	2.0	1.8	1.6	1.0
取付高さ	器具間隔最大限		2.5	3.8	3.4	3.1	2.8	3.5	3.1	2.8	2.6	2.9	2.6	2.4	2.2	2.4	2.1	2.0	1.8	1.2	
	横方向 (A)	縦方向 (B)	3.0	4.0	3.6	3.3	3.0	3.6	3.3	3.0	2.8	3.0	2.8	2.6	2.4	2.5	2.3	2.1	1.9	1.3	
H m	1.65 H m	1.55 H m	4.0	4.1	3.8	3.6	3.3	3.8	3.5	3.3	3.1	3.2	3.0	2.8	2.6	2.6	2.4	2.3	2.2	1.5	
			5.0	4.2	4.0	3.7	3.5	3.9	3.7	3.5	3.3	3.3	3.1	2.9	2.8	2.7	2.6	2.4	2.3	1.6	
			7.0	4.4	4.2	4.0	3.8	4.1	3.9	3.7	3.5	3.4	3.3	3.1	3.0	2.8	2.7	2.6	2.5	1.8	
			10.0	4.5	4.3	4.2	4.0	4.2	4.0	3.9	3.8	3.5	3.4	3.3	3.2	2.9	2.9	2.8	2.7	1.9	

