

屋内照明器具特性	
品番(品名)	LGW85014WZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0lm
管理番号	K0126055(1)DB1
BZ分類	BZ8/4.5/BZ7/8.5/BZ8

器具効率	70%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	27%	室指数	床	10%				10%				10%				10%				0%
下方光束	43%		照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.6	1.2	2.5	1.8	1.4	1.1	2.1	1.6	1.2	0.9	0.6
	中	0.6	0.8	3.8	2.9	2.3	1.9	3.5	2.7	2.2	1.8	3.0	2.3	1.9	1.5	2.5	2.0	1.6	1.3	0.9
	否	0.56	1.0	4.2	3.4	2.8	2.3	3.9	3.1	2.6	2.2	3.3	2.7	2.3	1.9	2.8	2.3	1.9	1.6	1.2
			1.25	4.6	3.8	3.2	2.7	4.3	3.6	3.0	2.6	3.6	3.1	2.6	2.3	3.1	2.6	2.3	2.0	1.4
下方投影面積		cm <sup>2</sup>	1.5	4.9	4.2	3.6	3.1	4.5	3.9	3.4	2.9	3.9	3.4	2.9	2.6	3.3	2.9	2.5	2.2	1.6
等価発光面積		cm <sup>2</sup>	2.0	5.3	4.7	4.1	3.7	4.9	4.4	3.9	3.5	4.2	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0
取付高さ	器具間隔最大限		2.5	5.6	5.0	4.5	4.1	5.2	4.7	4.2	3.9	4.5	4.1	3.7	3.4	3.8	3.5	3.2	3.0	2.2
	横方向(A)	縦方向(B)	3.0	5.8	5.2	4.8	4.4	5.4	4.9	4.5	4.2	4.7	4.3	4.0	3.7	4.0	3.7	3.4	3.2	2.4
Hm	1.91Hm	1.91Hm	4.0	6.0	5.6	5.2	4.9	5.6	5.2	4.9	4.6	4.9	4.6	4.3	4.0	4.2	4.0	3.7	3.5	2.7
			5.0	6.2	5.8	5.5	5.2	5.8	5.5	5.2	4.9	5.0	4.8	4.5	4.3	4.3	4.1	3.9	3.8	2.9
			7.0	6.4	6.1	5.8	5.6	6.0	5.7	5.5	5.2	5.2	5.0	4.8	4.6	4.5	4.4	4.2	4.1	3.2
			10.0	6.5	6.3	6.1	5.9	6.1	5.9	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	4.4	4.3	3.4

