

屋内照明器具特性	
品番(品名)	LGB81563Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0134318(0)DB1
BZ分類	BZ8/1.4/BZ7/1.8/BZ8/2.8/BZ7/8.5/BZ8

器具効率	57%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	22%	床	10%				10%				10%				10%				0%	
下方光束	35%		10%				10%				10%				10%				0%	
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	2.6	1.9	1.4	1.1	2.4	1.8	1.3	1.0	2.1	1.5	1.2	9	1.7	1.3	1.0	8	5
	中	0.6	0.8	3.1	2.4	1.9	1.5	2.9	2.2	1.8	1.5	2.4	1.9	1.6	1.3	2.1	1.6	1.3	1.1	8
	否	0.56	1.0	3.4	2.7	2.2	1.9	3.2	2.6	2.1	1.8	2.7	2.2	1.8	1.6	2.3	1.9	1.6	1.4	10
			1.25	3.7	3.1	2.6	2.2	3.5	2.9	2.5	2.1	3.0	2.5	2.1	1.9	2.5	2.1	1.9	1.6	1.2
下方投影面積	cm ²	1.5	4.0	3.4	2.9	2.5	3.7	3.1	2.7	2.4	3.2	2.7	2.4	2.1	2.7	2.3	2.1	1.8	1.3	
等価発光面積	cm ²	2.0	4.3	3.8	3.3	3.0	4.0	3.5	3.1	2.8	3.4	3.1	2.7	2.5	2.9	2.6	2.4	2.2	1.6	
取付高さ	器具間隔最大限		2.5	4.5	4.0	3.6	3.3	4.2	3.8	3.4	3.1	3.6	3.3	3.0	2.8	3.1	2.8	2.6	2.4	1.8
	横方向(A)	縦方向(B)	3.0	4.6	4.2	3.9	3.6	4.3	4.0	3.6	3.4	3.8	3.5	3.2	3.0	3.2	3.0	2.8	2.6	2.0
Hm	1.50Hm	1.50Hm	4.0	4.8	4.5	4.2	3.9	4.5	4.2	4.0	3.7	4.0	3.7	3.5	3.3	3.4	3.2	3.0	2.2	
			5.0	5.0	4.7	4.4	4.2	4.7	4.4	4.2	3.9	4.1	3.9	3.7	3.5	3.5	3.3	3.2	2.4	
			7.0	5.1	4.9	4.7	4.5	4.8	4.6	4.4	4.2	4.2	4.1	3.9	3.8	3.7	3.5	3.4	2.6	
			10.0	5.3	5.1	4.9	4.8	5.0	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.8	3.7	3.6	2.8	

