

# 屋内照明器具特性

品番 (品名)	L G W 4 5 8 8 0 Z																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m																
管理番号	K0123405 (1) DB1																
BZ分類	BZ10																

器具効率	35 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	18 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	17 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 ( X 0.01 ) Z C M																	
保守率	良	0.63	0.6	1.4	1.0	0.7	0.5	1.3	0.9	0.6	0.4	1.0	0.7	0.5	0.3	0.8	0.6	0.4	0.2	0.1
	中	0.6	0.8	1.7	1.3	1.0	0.7	1.6	1.2	0.9	0.7	1.3	0.9	0.7	0.5	1.0	0.7	0.5	0.4	0.2
	否	0.56	1.0	1.9	1.5	1.2	0.9	1.7	1.4	1.1	0.8	1.4	1.1	0.9	0.7	1.1	0.9	0.7	0.5	0.2
			1.25	2.1	1.7	1.4	1.1	1.9	1.5	1.3	1.0	1.6	1.3	1.0	0.8	1.2	1.0	0.8	0.7	0.3
下方投影面積		cm <sup>2</sup>	1.5	2.3	1.9	1.6	1.3	2.1	1.7	1.4	1.2	1.7	1.4	1.2	1.0	1.3	1.1	0.9	0.8	0.4
等価発光面積		cm <sup>2</sup>	2.0	2.5	2.1	1.8	1.6	2.3	1.9	1.7	1.5	1.8	1.6	1.4	1.2	1.5	1.3	1.1	1.0	0.6
取付高さ	器具間隔最大限		2.5	2.6	2.3	2.0	1.8	2.4	2.1	1.9	1.7	2.0	1.7	1.5	1.4	1.6	1.4	1.2	1.1	0.7
	横方向 (A)	縦方向 (B)	3.0	2.7	2.4	2.2	2.0	2.5	2.2	2.0	1.8	2.0	1.8	1.7	1.5	1.6	1.5	1.3	1.2	0.8
H m	0.00 H m	0.00 H m	4.0	2.8	2.6	2.4	2.2	2.6	2.4	2.2	2.0	2.2	2.0	1.8	1.7	1.8	1.6	1.5	1.4	0.9
			5.0	2.9	2.7	2.5	2.4	2.7	2.5	2.3	2.2	2.2	2.1	2.0	1.8	1.8	1.7	1.6	1.5	1.0
			7.0	3.0	2.9	2.7	2.6	2.8	2.7	2.5	2.4	2.4	2.2	2.1	2.0	1.9	1.8	1.7	1.7	1.1
			10.0	3.1	3.0	2.9	2.8	2.9	2.8	2.7	2.6	2.4	2.3	2.3	2.2	2.0	1.9	1.9	1.8	1.3

