

屋内照明器具特性

品番 (品名)	S F 9 9 9 Z																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m																
管理番号	K0169411(0)DR1																
BZ分類	BZ10																

器具効率	27 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	12 %	反射率	壁	0 %																
下方光束	15 %		床	10 %																
室指数	照明率 (X 0.01) ZCM																			
保守率	良	0.63	0.6	1.2	8	6	4	10	7	5	4	9	6	4	3	7	5	3	2	1
	中	0.6	0.8	1.4	10	8	6	12	9	7	6	10	8	6	5	8	6	5	4	2
	否	0.56	1.0	1.5	12	9	8	14	11	9	7	11	9	7	6	9	7	6	5	2
			1.25	1.7	14	11	9	15	12	10	9	13	10	9	7	10	8	7	6	3
下方投影面積	cm ²		1.5	1.8	15	13	11	16	14	12	10	14	11	10	8	11	9	8	7	4
等価発光面積	cm ²		2.0	2.0	17	15	13	18	15	14	12	15	13	11	10	12	11	9	8	5
取付高さ	器具間隔最大限		2.5	2.1	18	16	14	19	17	15	13	16	14	13	11	13	11	10	9	6
	横方向 (A)	縦方向 (B)	3.0	2.1	19	17	16	20	18	16	15	16	15	14	12	13	12	11	10	7
H m	0.00 H m	0.00 H m	4.0	2.2	2.1	1.9	1.7	2.1	1.9	1.8	1.6	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	8
			5.0	2.3	2.1	2.0	1.9	2.1	2.0	1.9	1.7	1.8	1.7	1.6	1.5	1.5	1.4	1.3	1.2	9
			7.0	2.4	2.3	2.1	2.0	2.2	2.1	2.0	1.9	1.9	1.8	1.7	1.6	1.6	1.5	1.4	1.4	10
			10.0	2.4	2.4	2.3	2.2	2.3	2.2	2.1	2.0	1.9	1.9	1.8	1.7	1.6	1.6	1.5	1.5	11

