

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 0 3 B K	
光源	LDA3L-E17/C/W x1	280.0 lm
管理番号	K0133085(0)DB1	
BZ分類	BZ4/0.7/BZ5	

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		18%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		68%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	48	38	32	27	46	37	31	27	42	34	29	25	39	32	28	24	22	
	中	0.63	0.8	55	45	39	34	53	44	38	33	48	41	36	32	44	38	34	30	27	
	否	0.56	1.0	60	51	44	39	57	49	43	38	52	46	40	36	48	42	38	35	31	
			1.25	65	56	50	45	62	54	48	44	57	50	46	42	52	47	43	39	35	
下方投影面積	c m <sup>2</sup>		1.5	68	60	54	49	65	58	53	48	60	54	49	46	55	50	46	43	38	
	等価発光面積		c m <sup>2</sup>	2.0	73	66	61	56	70	64	59	55	64	59	55	52	59	55	52	49	43
取付高さ	器具間隔最大限		2.5	76	70	65	61	73	67	63	59	67	63	59	56	61	58	55	52	47	
	横方向 (A)	縦方向 (B)	3.0	78	73	68	64	75	70	66	63	69	65	62	59	63	60	58	55	49	
H <sub>m</sub>	1.31H <sub>m</sub>	1.28H <sub>m</sub>	4.0	80	76	73	69	77	74	70	67	71	68	66	63	66	63	61	59	53	
			5.0	82	79	75	73	79	76	73	70	73	70	68	66	67	65	64	62	55	
			7.0	84	81	79	77	81	78	76	74	75	73	71	70	69	68	66	65	58	
			10.0	85	84	82	80	82	81	79	77	77	75	74	72	71	70	69	68	61	

