

屋内照明器具特性

品番 (品名)	LGW75000Z														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 lm														
管理番号	K0189045(5)DR1														
BZ分類	BZ10														

器具効率	26%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	13%	壁	10%				10%				10%				10%				0%	
下方光束	13%	床	10%				10%				10%				10%				0%	
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.69	0.6	11	7	5	4	10	7	5	3	8	5	4	3	6	4	3	2	0
	中	0.67	0.8	13	9	7	5	12	9	6	5	9	7	5	4	7	5	4	3	1
	否	0.63	1.0	14	11	9	7	13	10	8	6	10	8	6	5	8	6	5	4	2
			1.25	16	13	10	8	14	12	9	8	12	9	8	6	9	7	6	5	2
下方投影面積	cm ²		1.5	17	14	12	10	15	13	11	9	12	10	9	7	10	8	7	6	3
等価発光面積	cm ²		2.0	18	16	14	12	17	14	13	11	14	12	10	9	11	9	8	7	4
取付高さ	器具間隔最大限		2.5	20	17	15	13	18	16	14	12	15	13	12	10	12	10	9	8	5
	横方向 (A)	縦方向 (B)	3.0	20	18	16	15	19	17	15	14	15	14	12	11	12	11	10	9	6
Hm	0.00Hm	0.20Hm	4.0	21	19	18	16	19	18	16	15	16	15	14	13	13	12	11	10	7
			5.0	22	20	19	18	20	19	17	16	17	16	15	14	14	13	12	11	7
			7.0	23	21	20	19	21	20	19	18	18	17	16	15	14	14	13	12	8
			10.0	23	22	21	21	22	21	20	19	18	18	17	16	15	14	14	13	9

