

屋内照明器具特性	
品番 (品名)	LGW85010Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0126467(0)DR1
BZ分類	BZ8

器具効率	67%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	34%	床	10%				10%				10%				10%				0%				
下方光束	33%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	3.0	2.2	1.7	1.3	2.7	2.0	1.5	1.2	2.3	1.7	1.3	1.0	1.8	1.4	1.0	0.8	0.5			
	中	0.6	0.8	3.6	2.7	2.2	1.8	3.2	2.5	2.0	1.7	2.7	2.1	1.7	1.4	2.1	1.7	1.4	1.1	0.7			
	否	0.56	1.0	3.9	3.2	2.6	2.2	3.6	2.9	2.4	2.0	3.0	2.4	2.0	1.7	2.4	2.0	1.7	1.4	0.9			
			1.25	4.3	3.6	3.0	2.6	3.9	3.3	2.8	2.4	3.2	2.7	2.4	2.0	2.6	2.2	1.9	1.7	1.1			
下方投影面積		cm ²	1.5	4.6	3.9	3.4	2.9	4.2	3.6	3.1	2.7	3.5	3.0	2.6	2.3	2.8	2.4	2.1	1.9	1.2			
等価発光面積		cm ²	2.0	4.9	4.3	3.9	3.5	4.5	4.0	3.6	3.2	3.8	3.4	3.0	2.7	3.0	2.7	2.5	2.2	1.5			
取付高さ	器具間隔最大限		2.5	5.2	4.7	4.2	3.8	4.8	4.3	3.9	3.6	4.0	3.6	3.3	3.0	3.2	2.9	2.7	2.5	1.7			
	横方向 (A)	縦方向 (B)	3.0	5.4	4.9	4.5	4.1	4.9	4.5	4.1	3.8	4.1	3.8	3.5	3.2	3.4	3.1	2.9	2.7	1.8			
Hm	1.38Hm	1.46Hm	4.0	5.6	5.2	4.8	4.5	5.2	4.8	4.5	4.2	4.3	4.1	3.8	3.6	3.5	3.3	3.1	3.0	2.0			
			5.0	5.7	5.4	5.1	4.8	5.3	5.0	4.7	4.5	4.5	4.2	4.0	3.8	3.7	3.5	3.3	3.2	2.2			
			7.0	5.9	5.7	5.4	5.2	5.5	5.2	5.0	4.8	4.6	4.4	4.3	4.1	3.8	3.7	3.6	3.4	2.4			
			10.0	6.1	5.9	5.7	5.5	5.6	5.4	5.3	5.1	4.8	4.6	4.5	4.4	4.0	3.9	3.7	3.6	2.6			

