

屋内照明器具特性	
品番 (品名)	L G W 8 5 1 0 0 B Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0128279(2)DB1
BZ分類	BZ5/0.7/BZ4

器具効率	25%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	25%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.63	0.6	14	11	9	8	14	11	9	8	13	11	9	8	13	10	9	8	7	
	中 0.6	0.8	17	14	12	11	16	14	12	10	16	13	12	10	15	13	11	10	10	
	否 0.56	1.0	18	16	14	12	18	15	14	12	17	15	13	12	16	15	13	12	12	
		1.25	20	17	16	14	19	17	15	14	19	17	15	14	18	16	15	14	13	
下方投影面積	cm <sup>2</sup>	1.5	21	19	17	16	20	18	17	16	19	18	17	15	19	17	16	15	15	
等価発光面積	cm <sup>2</sup>	2.0	22	20	19	18	22	20	19	18	21	20	18	17	20	19	18	17	17	
取付高さ	器具間隔最大限		2.5	23	21	20	19	22	21	20	19	22	21	20	19	21	20	19	18	18
	横方向 (A)	縦方向 (B)	3.0	23	22	21	20	23	22	21	20	22	21	20	20	22	21	20	19	19
1.5m	1.85 m	1.87 m	4.0	24	23	22	21	24	23	22	21	23	22	22	21	22	22	21	21	20
2	2.45	2.47	5.0	25	24	23	22	24	23	23	22	24	23	22	22	23	22	22	21	21
2.5	3.07	3.09	7.0	25	24	24	23	25	24	24	23	24	24	23	23	24	23	23	22	22
3	3.68	3.71	10.0	25	25	25	24	25	25	24	24	25	24	24	24	24	24	23	23	22

