

屋内照明器具特性

| | | | | | | | | | | |
|---------|------------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | LGB87026Z | | | | | | | | | |
| 光源 | LDA4L-H-E17/E/S/W/2 ×1 | | | | | 440.0 1 m | | | | |
| 管理番号 | K0122402 (1) DB 1 | | | | | | | | | |
| BZ分類 | BZ3/2.3/BZ4 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|---------------|---------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|-----|-----|-----|
| 器具効率 | 64 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | | |
| | 上方光束 | | 17 % | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % |
| | 下方光束 | | 47 % | | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 3.6 | 2.9 | 2.5 | 2.2 | 3.5 | 2.8 | 2.4 | 2.1 | 3.2 | 2.6 | 2.3 | 2.0 | 2.9 | 2.5 | 2.2 | 1.9 | 1.7 | |
| | 中 | 0.63 | 0.8 | 4.2 | 3.6 | 3.1 | 2.8 | 4.0 | 3.5 | 3.0 | 2.7 | 3.7 | 3.2 | 2.9 | 2.6 | 3.4 | 3.0 | 2.7 | 2.5 | 2.2 | |
| | 否 | 0.56 | 1.0 | 4.6 | 4.0 | 3.6 | 3.3 | 4.4 | 3.9 | 3.5 | 3.2 | 4.0 | 3.6 | 3.3 | 3.0 | 3.7 | 3.3 | 3.1 | 2.8 | 2.5 | |
| | | | 1.25 | 5.0 | 4.4 | 4.0 | 3.7 | 4.7 | 4.3 | 3.9 | 3.6 | 4.3 | 3.9 | 3.6 | 3.4 | 3.9 | 3.6 | 3.4 | 3.2 | 2.8 | |
| 下方投影面積 | | | 1.5 | 5.2 | 4.7 | 4.3 | 4.0 | 5.0 | 4.5 | 4.2 | 3.9 | 4.5 | 4.2 | 3.9 | 3.7 | 4.1 | 3.9 | 3.6 | 3.5 | 3.1 | |
| | 等価発光面積 | | 2.0 | 5.5 | 5.1 | 4.8 | 4.5 | 5.3 | 4.9 | 4.6 | 4.4 | 4.8 | 4.5 | 4.3 | 4.1 | 4.4 | 4.2 | 4.0 | 3.8 | 3.4 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 5.7 | 5.4 | 5.1 | 4.8 | 5.5 | 5.1 | 4.9 | 4.7 | 5.0 | 4.8 | 4.5 | 4.4 | 4.6 | 4.4 | 4.2 | 4.1 | 3.6 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 5.8 | 5.5 | 5.3 | 5.0 | 5.6 | 5.3 | 5.1 | 4.9 | 5.1 | 4.9 | 4.7 | 4.6 | 4.7 | 4.5 | 4.4 | 4.2 | 3.7 | |
| Hm | 1.06Hm | 1.44Hm | 4.0 | 6.0 | 5.8 | 5.6 | 5.4 | 5.8 | 5.5 | 5.4 | 5.2 | 5.3 | 5.1 | 5.0 | 4.8 | 4.8 | 4.7 | 4.6 | 4.5 | 3.9 | |
| | | | 5.0 | 6.1 | 5.9 | 5.7 | 5.6 | 5.9 | 5.7 | 5.5 | 5.4 | 5.4 | 5.2 | 5.1 | 5.0 | 4.9 | 4.8 | 4.7 | 4.6 | 4.1 | |
| | | | 7.0 | 6.2 | 6.1 | 5.9 | 5.8 | 6.0 | 5.8 | 5.7 | 5.6 | 5.5 | 5.4 | 5.3 | 5.2 | 5.0 | 5.0 | 4.9 | 4.8 | 4.2 | |
| | | | 10.0 | 6.3 | 6.2 | 6.1 | 6.0 | 6.1 | 6.0 | 5.9 | 5.8 | 5.6 | 5.5 | 5.4 | 5.4 | 5.1 | 5.1 | 5.0 | 5.0 | 4.3 | |

