

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 3 2 B U
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0123403 ( 1 ) DB 1
B Z 分類	BZ9 / 3.5 / BZ8

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	24 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	33 %		10 %				10 %				10 %				10 %				0 %	
室指数		照明率 ( X0.01 )																Z C M		
保守率	良	0.63	0.6	2.5	1.8	1.3	1.0	2.3	1.6	1.2	9	1.9	1.4	1.0	8	1.6	1.1	8	6	4
	中	0.6	0.8	3.0	2.3	1.8	1.4	2.7	2.1	1.6	1.3	2.3	1.8	1.4	1.1	1.9	1.5	1.2	9	6
	否	0.56	1.0	3.3	2.6	2.1	1.7	3.1	2.4	2.0	1.6	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.2	8
			1.25	3.6	3.0	2.5	2.1	3.4	2.8	2.3	2.0	2.8	2.4	2.0	1.7	2.3	2.0	1.7	1.4	1.0
下方投影面積		cm <sup>2</sup>	1.5	3.9	3.3	2.8	2.4	3.6	3.0	2.6	2.2	3.0	2.6	2.2	1.9	2.5	2.2	1.9	1.6	1.1
等価発光面積		cm <sup>2</sup>	2.0	4.2	3.7	3.2	2.9	3.9	3.4	3.0	2.7	3.3	2.9	2.6	2.3	2.7	2.4	2.2	2.0	1.4
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.2	4.1	3.7	3.3	3.0	3.5	3.1	2.9	2.6	2.9	2.7	2.4	2.2	1.6
	横方向 ( A )	縦方向 ( B )	3.0	4.6	4.2	3.8	3.5	4.3	3.9	3.5	3.2	3.6	3.3	3.1	2.8	3.1	2.8	2.6	2.4	1.7
H m	1.59 H m	2.31 H m	4.0	4.8	4.4	4.1	3.8	4.5	4.1	3.8	3.6	3.8	3.6	3.3	3.1	3.2	3.0	2.8	2.7	2.0
			5.0	4.9	4.6	4.3	4.1	4.6	4.3	4.1	3.8	4.0	3.7	3.5	3.3	3.4	3.2	3.0	2.9	2.1
			7.0	5.1	4.8	4.6	4.4	4.8	4.5	4.3	4.1	4.1	3.9	3.8	3.6	3.5	3.4	3.2	3.1	2.4
			10.0	5.2	5.0	4.9	4.7	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.6	3.5	3.4	3.3	2.5

