

| | |
|----------|----------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGW85010Z |
| 光源 | LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m |
| 管理番号 | K0126467(0)DR1 |
| BZ分類 | BZ8 |

| | | | | | | | | | | | | | | | | | | | | | | |
|--------|---------------------------|----------|-------------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|--|--|--|
| 器具効率 | 67% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | | | |
| 上方光束 | 34% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | | | |
| 下方光束 | 33% | 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 0.63 中 0.6 否 0.56 | 0.6 | 30 | 22 | 17 | 13 | 27 | 20 | 15 | 12 | 23 | 17 | 13 | 10 | 18 | 14 | 10 | 8 | 5 | | | |
| | | 0.8 | 36 | 27 | 22 | 18 | 32 | 25 | 20 | 17 | 27 | 21 | 17 | 14 | 21 | 17 | 14 | 11 | 7 | | | |
| | | 1.0 | 39 | 32 | 26 | 22 | 36 | 29 | 24 | 20 | 30 | 24 | 20 | 17 | 24 | 20 | 17 | 14 | 9 | | | |
| | | 1.25 | 43 | 36 | 30 | 26 | 39 | 33 | 28 | 24 | 32 | 27 | 24 | 20 | 26 | 22 | 19 | 17 | 11 | | | |
| 下方投影面積 | c m ² | 1.5 | 46 | 39 | 34 | 29 | 42 | 36 | 31 | 27 | 35 | 30 | 26 | 23 | 28 | 24 | 21 | 19 | 12 | | | |
| | | 2.0 | 49 | 43 | 39 | 35 | 45 | 40 | 36 | 32 | 38 | 34 | 30 | 27 | 30 | 27 | 25 | 22 | 15 | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 52 | 47 | 42 | 38 | 48 | 43 | 39 | 36 | 40 | 36 | 33 | 30 | 32 | 29 | 27 | 17 | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 54 | 49 | 45 | 41 | 49 | 45 | 41 | 38 | 41 | 38 | 35 | 32 | 34 | 31 | 29 | 18 | | | |
| H m | 1.38 H m | 1.46 H m | 4.0 | 56 | 52 | 48 | 45 | 52 | 48 | 45 | 42 | 43 | 41 | 38 | 36 | 35 | 33 | 31 | 20 | | | |
| | | | 5.0 | 57 | 54 | 51 | 48 | 53 | 50 | 47 | 45 | 45 | 42 | 40 | 38 | 37 | 35 | 33 | 22 | | | |
| | | | 7.0 | 59 | 57 | 54 | 52 | 55 | 52 | 50 | 48 | 46 | 44 | 43 | 41 | 38 | 37 | 36 | 24 | | | |
| | | | 10.0 | 61 | 59 | 57 | 55 | 56 | 54 | 53 | 51 | 48 | 46 | 45 | 44 | 40 | 39 | 37 | 26 | | | |

