

屋内照明器具特性	
品番 (品名)	L G W 8 5 1 0 2 B Z
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0169572 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率	25 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	25 %		床	10 %				10 %				10 %				10 %				0 %
器具効率	25 %	室指数	照明率 (X0.01)																Z C M	
保守率	良 0.63	0.6	14	11	9	8	14	11	9	8	13	11	9	8	13	11	9	8	7	
	中 0.6	0.8	17	14	12	11	17	14	12	11	16	14	12	11	15	13	12	11	10	
	否 0.56	1.0	19	16	14	13	18	16	14	13	17	15	14	13	17	15	14	12	12	
		1.25	20	18	16	15	20	18	16	15	19	17	16	14	18	17	15	14	14	
下方投影面積	c m ²	1.5	21	19	17	16	21	19	17	16	20	18	17	16	19	18	17	16	15	
等価発光面積		2.0	23	21	19	18	22	20	19	18	21	20	19	18	21	19	18	18	17	
取付		器具間隔最大限	2.5	23	22	21	20	23	22	20	19	22	21	20	19	22	21	20	19	18
高さ		横方向 (A)	縦方向 (B)	3.0	24	23	22	21	24	22	21	20	23	22	21	20	22	21	21	20
H m	1.25 H m	1.26 H m	4.0	25	24	23	22	24	23	23	22	24	23	22	22	23	22	22	21	21
			5.0	25	24	24	23	25	24	23	23	24	24	23	22	24	23	22	22	21
			7.0	26	25	25	24	25	25	24	24	25	24	24	23	24	24	23	23	22
			10.0	26	26	25	25	26	25	25	25	25	25	24	24	25	24	24	24	23

