

# 屋内照明器具特性

品番 (品名)	LSEB4028	
光源	LED5000_70_460 ×1	460.0 l m
管理番号	K0151935 ( 0 ) DB 1	
BZ分類	BZ6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		28 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		72 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	4.9	3.6	2.8	2.3	4.6	3.5	2.7	2.2	4.1	3.1	2.5	2.0	3.6	2.8	2.3	1.9	1.5	
	中	0.6	0.8	5.8	4.6	3.8	3.2	5.5	4.4	3.6	3.0	4.9	4.0	3.3	2.8	4.3	3.6	3.0	2.6	2.1	
	否	0.56	1.0	6.4	5.3	4.4	3.8	6.1	5.0	4.3	3.7	5.4	4.5	3.9	3.4	4.8	4.1	3.5	3.1	2.6	
			1.25	7.0	5.9	5.1	4.5	6.6	5.6	4.9	4.3	5.9	5.1	4.5	4.0	5.2	4.6	4.1	3.7	3.0	
下方投影面積	c m <sup>2</sup>		1.5	7.4	6.4	5.7	5.0	7.0	6.1	5.4	4.8	6.3	5.5	4.9	4.5	5.6	5.0	4.5	4.1	3.4	
	等価発光面積		c m <sup>2</sup>	2.0	8.0	7.1	6.4	5.8	7.6	6.8	6.2	5.6	6.8	6.1	5.6	5.2	6.0	5.5	5.1	4.7	4.0
取付高さ	器具間隔最大限		2.5	8.4	7.6	7.0	6.4	7.9	7.2	6.7	6.2	7.1	6.6	6.1	5.7	6.4	5.9	5.5	5.2	4.4	
	横方向 (A)	縦方向 (B)	3.0	8.6	7.9	7.4	6.9	8.2	7.6	7.1	6.6	7.4	6.9	6.4	6.1	6.6	6.2	5.9	5.5	4.7	
H m	1.46 H m	1.46 H m	4.0	9.0	8.4	7.9	7.5	8.5	8.0	7.6	7.2	7.7	7.3	6.9	6.6	6.9	6.6	6.3	6.0	5.1	
			5.0	9.2	8.7	8.3	7.9	8.7	8.3	7.9	7.6	7.9	7.6	7.3	7.0	7.1	6.8	6.6	6.4	5.4	
			7.0	9.4	9.1	8.7	8.4	9.0	8.7	8.4	8.1	8.2	7.9	7.7	7.4	7.4	7.2	7.0	6.8	5.8	
			10.0	9.6	9.4	9.1	8.9	9.2	9.0	8.7	8.5	8.4	8.2	8.0	7.8	7.6	7.4	7.3	7.1	6.1	

