

# 屋内照明器具特性

品番 (品名)	LSEB3112K	
光源	LDG11L-G/95/W x1	1370.0 lm
管理番号	K0147988(0)DB1	
BZ分類	BZ6	

器具効率	70%	天井	80%				70%				50%				30%				0%		
	上方光束		4%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		66%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	3.6	2.6	2.1	1.6	3.5	2.6	2.0	1.6	3.2	2.5	2.0	1.6	3.0	2.4	1.9	1.6	1.4	
	中	0.63	0.8	4.3	3.4	2.7	2.3	4.1	3.3	2.7	2.3	3.8	3.1	2.6	2.2	3.6	3.0	2.5	2.2	2.0	
	否	0.56	1.0	4.7	3.9	3.2	2.8	4.6	3.8	3.2	2.7	4.3	3.6	3.1	2.7	4.0	3.4	3.0	2.6	2.4	
			1.25	5.1	4.3	3.7	3.3	5.0	4.2	3.7	3.2	4.7	4.0	3.6	3.2	4.4	3.9	3.4	3.1	2.8	
下方投影面積	cm <sup>2</sup>		1.5	5.4	4.7	4.1	3.7	5.3	4.6	4.1	3.6	5.0	4.4	3.9	3.5	4.7	4.2	3.8	3.4	3.2	
	等価発光面積		2.0	5.9	5.2	4.7	4.3	5.7	5.1	4.6	4.2	5.4	4.9	4.5	4.1	5.1	4.6	4.3	4.0	3.7	
取付高さ	器具間隔最大限		2.5	6.1	5.6	5.1	4.7	6.0	5.4	5.0	4.6	5.6	5.2	4.8	4.5	5.3	5.0	4.6	4.4	4.1	
	横方向 (A)	縦方向 (B)	3.0	6.3	5.8	5.4	5.0	6.2	5.7	5.3	4.9	5.8	5.4	5.1	4.8	5.5	5.2	4.9	4.7	4.4	
Hm	1.45Hm	1.45Hm	4.0	6.6	6.2	5.8	5.5	6.4	6.0	5.7	5.4	6.1	5.8	5.5	5.2	5.8	5.5	5.3	5.1	4.7	
			5.0	6.7	6.4	6.1	5.8	6.6	6.2	6.0	5.7	6.3	6.0	5.7	5.5	6.0	5.7	5.5	5.3	5.0	
			7.0	6.9	6.6	6.4	6.2	6.8	6.5	6.3	6.1	6.5	6.2	6.0	5.9	6.2	6.0	5.8	5.7	5.3	
			10.0	7.1	6.9	6.7	6.5	6.9	6.7	6.5	6.4	6.6	6.5	6.3	6.2	6.3	6.2	6.1	6.0	5.6	

