

屋内照明器具特性	
品番 (品名)	LSEW4002YZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0124141(1)DB1
BZ分類	BZ9/4.5/BZ8

器具効率	48%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	24%	室指数	床	10%				10%				10%				10%				0%	
下方光束	24%		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	0.6	21	15	11	8	19	14	10	8	16	11	8	6	12	9	7	5	3	
	中 0.6		0.8	25	19	15	12	23	18	14	11	19	14	12	9	15	12	9	7	4	
	否 0.56		1.0	28	22	18	15	25	20	17	14	21	17	14	12	17	14	11	9	5	
			1.25	31	25	21	18	28	23	19	17	23	19	16	14	18	15	13	11	7	
下方投影面積	cm ²	等価発光面積	1.5	33	27	24	20	30	25	22	19	24	21	18	16	20	17	15	13	8	
	cm ²		2.0	35	31	27	24	32	28	25	22	27	24	21	19	22	19	17	16	10	
取付高さ	器具間隔最大限		2.5	37	33	30	27	34	31	28	25	28	26	23	21	23	21	19	17	11	
Hm	1.60Hm		縦方向(B)	3.0	38	35	32	29	35	32	29	27	29	27	25	23	24	22	20	19	13
		横方向(A)	4.0	40	37	35	32	37	34	32	30	31	29	27	25	25	24	22	21	14	
			5.0	41	39	36	34	38	36	34	32	32	30	29	27	26	25	24	23	16	
			7.0	42	40	39	37	39	38	36	34	33	32	31	29	27	26	25	24	17	
			10.0	43	42	41	39	40	39	38	37	34	33	32	31	28	28	27	26	19	

