

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | NTS62832S+NTS90101 |          |
| 光源      | LED3500_70_395 ×1  | 395.0 1m |
| 管理番号    | K0155952(5)DJ1     |          |
| BZ分類    | BZ1                |          |

|                  |                 |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|------------------|-----------------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率             | 101%            | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|                  | 上方光束<br>0%      |                 | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束             | 101%            | 床               |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 室指数              | 照明率 ( X0.01 )   |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率              | 良 0.67          | 0.6             | 0.6  | 91  | 86  | 83  | 81  | 90  | 86  | 83  | 81  | 89  | 85  | 83  | 81  | 88  | 85  | 82  | 81  | 80  |
|                  | 中 0.63          |                 | 0.8  | 95  | 91  | 88  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 88  | 86  | 92  | 89  | 87  | 86  | 85  |
|                  | 否 0.56          |                 | 1.0  | 98  | 94  | 92  | 90  | 97  | 94  | 91  | 89  | 96  | 93  | 91  | 89  | 95  | 92  | 90  | 89  | 88  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | cm <sup>2</sup> | 1.25 | 100 | 97  | 95  | 93  | 99  | 96  | 94  | 92  | 98  | 95  | 93  | 92  | 96  | 94  | 93  | 91  | 90  |
|                  |                 |                 | 1.5  | 102 | 99  | 96  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 94  | 98  | 96  | 94  | 93  | 92  |
|                  |                 |                 | 2.0  | 103 | 101 | 99  | 98  | 102 | 100 | 99  | 97  | 101 | 99  | 97  | 96  | 99  | 98  | 96  | 95  | 94  |
| 取付高さ             | 器具間隔最大限         |                 | 2.5  | 104 | 102 | 101 | 99  | 104 | 102 | 100 | 99  | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 97  | 95  |
|                  | 横方向 (A)         | 縦方向 (B)         | 3.0  | 105 | 103 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 101 | 100 | 99  | 98  | 96  |
| Hm               | 0.47Hm          | 0.47Hm          | 4.0  | 106 | 105 | 104 | 102 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 100 | 99  | 97  |
|                  |                 |                 | 5.0  | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 98  |
|                  |                 |                 | 7.0  | 107 | 106 | 106 | 105 | 106 | 105 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 102 | 101 | 101 | 98  |
|                  |                 |                 | 10.0 | 108 | 107 | 107 | 106 | 107 | 106 | 106 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 102 | 101 | 99  |

