

屋内照明器具特性

品番(品名)	NTS62713S+NTS90201	
光源	LED3000_70_805 x1	805.0 lm
管理番号	K0156488(1)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		下方光束 102%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																			ZCM	
保守率	良 0.67	中 0.63	否 0.56	0.6	1.02	1.00	0.98	0.97	1.02	1.00	0.98	0.97	1.01	0.99	0.98	0.97	1.01	0.99	0.98	0.97	0.96
	1.0			1.05	1.03	1.02	1.00	1.05	1.03	1.01	1.00	1.03	1.02	1.01	1.00	1.03	1.01	1.00	0.99	0.98	0.98
	1.25			1.06	1.04	1.03	1.02	1.05	1.04	1.03	1.01	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	0.99
下方投影面積 等価発光面積	cm ²	cm ²	1.5	1.07	1.05	1.04	1.03	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.00	1.00	
	2.0		1.08	1.06	1.05	1.04	1.07	1.05	1.04	1.03	1.05	1.04	1.03	1.03	1.04	1.03	1.02	1.01	1.00	1.00	
取付高さ	器具間隔最大限		2.5	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.01	
	Hm	0.25Hm	0.25Hm	3.0	1.09	1.07	1.06	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.01	
Hm	0.25Hm	0.25Hm	4.0	1.09	1.08	1.07	1.07	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01	
			5.0	1.09	1.09	1.08	1.07	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01	
Hm	0.25Hm	0.25Hm	7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.03	1.01	
			10.0	1.10	1.10	1.09	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.03	1.01	

