

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK82730+NNL8000ENC         |
| 光源       | LED5000_85_9690 ×1 9690.0 lm |
| 管理番号     | K0130922 (5) DB1             |
| BZ分類     | BZ5                          |

| 器具効率     |           |        | 100 %           |        | 反射率             | 天井  | 80 %              |     |     |    | 70 % |     |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|--------|-----------------|--------|-----------------|-----|-------------------|-----|-----|----|------|-----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |        |                 |        |                 | 壁   | 70                | 50  | 30  | 10 | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |        |                 |        |                 | 床   | 10 %              |     |     |    | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |        |                 |        |                 | 室指数 | 照明率 ( X0.01 ) ZCM |     |     |    |      |     |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           |        | 良<br>中<br>否     | 0.81   | 0.6             | 56  | 43                | 35  | 29  | 54 | 42   | 35  | 29 | 52 | 41   | 34 | 29 | 50 | 40   | 34 | 29 | 27 |     |
|          |           |        |                 | 0.77   | 0.8             | 66  | 54                | 46  | 40  | 64 | 53   | 45  | 40 | 61 | 51   | 45 | 39 | 59 | 50   | 44 | 39 | 37 |     |
|          |           |        |                 | 0.68   | 1.0             | 72  | 61                | 53  | 47  | 71 | 60   | 53  | 47 | 68 | 59   | 52 | 47 | 65 | 57   | 51 | 46 | 44 |     |
|          |           |        |                 |        | 1.25            | 78  | 68                | 60  | 55  | 77 | 67   | 60  | 54 | 73 | 65   | 59 | 54 | 70 | 64   | 58 | 53 | 51 |     |
| 下方投影面積   |           |        | cm <sup>2</sup> | 1.5    | 82              | 73  | 66                | 60  | 81  | 72 | 65   | 60  | 78 | 70 | 64   | 59 | 75 | 68 | 63   | 59 | 56 |    |     |
|          |           |        |                 | 等価発光面積 | cm <sup>2</sup> | 2.0 | 88                | 81  | 74  | 69 | 87   | 79  | 73 | 69 | 83   | 77 | 72 | 68 | 80   | 75 | 71 | 67 | 64  |
| 取付<br>高さ | 器具間隔最大限   |        |                 | 2.5    | 92              | 85  | 80                | 75  | 90  | 84 | 79   | 74  | 87 | 82 | 77   | 73 | 84 | 80 | 76   | 73 | 70 |    |     |
|          | 横方向 ( A ) |        | 縦方向 ( B )       | 3.0    | 95              | 89  | 84                | 79  | 93  | 88 | 83   | 79  | 90 | 85 | 81   | 78 | 87 | 83 | 80   | 77 | 74 |    |     |
| 1.5m     | 2.09 m    | 2.88 m | 4.0             | 98     | 93              | 89  | 86                | 96  | 92  | 88 | 85   | 93  | 90 | 87 | 84   | 91 | 88 | 85 | 82   | 80 |    |    |     |
| 2        | 2.72      | 3.31   | 5.0             | 100    | 96              | 93  | 89                | 98  | 95  | 92 | 89   | 96  | 93 | 90 | 87   | 93 | 90 | 88 | 86   | 83 |    |    |     |
| 2.5      | 3.35      | 3.8    | 7.0             | 102    | 99              | 97  | 94                | 101 | 98  | 96 | 93   | 98  | 96 | 94 | 92   | 96 | 94 | 92 | 90   | 87 |    |    |     |
| 3        | 3.99      | 4.33   | 10.0            | 104    | 102             | 100 | 98                | 103 | 101 | 99 | 97   | 100 | 98 | 97 | 96   | 98 | 96 | 95 | 94   | 91 |    |    |     |

