

|          |   |
|----------|---|
| 屋内照明器具特性 |   |
| 品番 (品名)  | LGW51784                                |
| 光源       | LED5000_70_1010 x1 1010.0 1m            |
| 管理番号     | K0161585(0)DB1                          |
| BZ分類     | BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5<br>/6.0/BZ6 |

|        |         |         |             |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |  |  |     |
|--------|---------|---------|-------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|--|--|-----|
| 器具効率   | 100%    | 天井      | 80%         |     |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |  |  |     |
|        |         | 壁       | 70          | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |  |  |     |
| 上方光束   | 14%     | 床       | 10%         |     |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |  |  |     |
| 下方光束   | 86%     | 室指数     | 照明率 (X0.01) |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |  |  | ZCM |
| 保守率    | 良       | 0.63    | 0.6         | 53  | 40 | 32 | 27  | 51 | 39 | 31 | 26  | 47 | 37 | 30 | 25  | 43 | 35 | 29 | 24 | 21 |  |  |     |
|        | 中       | 0.6     | 0.8         | 62  | 50 | 42 | 36  | 60 | 49 | 41 | 35  | 55 | 46 | 39 | 34  | 51 | 43 | 37 | 33 | 29 |  |  |     |
|        | 否       | 0.56    | 1.0         | 68  | 57 | 49 | 43  | 66 | 55 | 48 | 42  | 61 | 52 | 46 | 41  | 57 | 49 | 43 | 39 | 35 |  |  |     |
|        |         |         | 1.25        | 74  | 64 | 56 | 50  | 71 | 62 | 55 | 49  | 66 | 58 | 52 | 47  | 62 | 55 | 50 | 45 | 41 |  |  |     |
| 下方投影面積 |         |         | 1.5         | 78  | 69 | 61 | 55  | 76 | 67 | 60 | 54  | 70 | 63 | 57 | 52  | 65 | 59 | 54 | 50 | 45 |  |  |     |
|        |         |         | 2.0         | 84  | 76 | 69 | 64  | 81 | 74 | 67 | 62  | 76 | 69 | 64 | 60  | 70 | 65 | 61 | 57 | 52 |  |  |     |
| 取付高さ   | 器具間隔最大限 |         | 2.5         | 88  | 80 | 74 | 69  | 85 | 78 | 73 | 68  | 79 | 74 | 69 | 65  | 74 | 69 | 66 | 62 | 57 |  |  |     |
|        | 横方向 (A) | 縦方向 (B) | 3.0         | 90  | 84 | 78 | 74  | 87 | 81 | 76 | 72  | 82 | 77 | 73 | 69  | 76 | 72 | 69 | 66 | 60 |  |  |     |
| Hm     | 1.31Hm  | 1.31Hm  | 4.0         | 94  | 88 | 84 | 80  | 91 | 86 | 82 | 78  | 85 | 81 | 78 | 74  | 80 | 77 | 74 | 71 | 65 |  |  |     |
|        |         |         | 5.0         | 96  | 91 | 87 | 84  | 93 | 89 | 85 | 82  | 87 | 84 | 81 | 78  | 82 | 79 | 77 | 74 | 68 |  |  |     |
|        |         |         | 7.0         | 98  | 95 | 92 | 89  | 95 | 92 | 89 | 87  | 90 | 87 | 85 | 83  | 84 | 82 | 80 | 79 | 72 |  |  |     |
|        |         |         | 10.0        | 100 | 97 | 95 | 93  | 97 | 95 | 93 | 91  | 92 | 90 | 88 | 86  | 87 | 85 | 84 | 82 | 76 |  |  |     |

