

屋内照明器具特性

品番 (品名)	L G W 8 0 2 1 2 K									
光源	LED2700_70_380 ×1					380.0 l m				
管理番号	K0158607 (0) DB 1									
B Z 分類	B Z 8 / 0.9 / B Z 7									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %	室指数	照明率 (X 0.01)																Z C M	
保守率	良	0.63	0.6	4.6	3.3	2.5	2.0	4.2	3.1	2.4	1.8	3.4	2.6	2.0	1.6	2.8	2.1	1.6	1.3	0.8
	中	0.6	0.8	5.4	4.2	3.4	2.8	4.9	3.9	3.1	2.6	4.1	3.2	2.7	2.2	3.3	2.7	2.2	1.8	1.2
	否	0.56	1.0	6.0	4.8	4.0	3.4	5.5	4.5	3.7	3.2	4.5	3.8	3.2	2.7	3.7	3.1	2.6	2.2	1.4
			1.25	6.5	5.5	4.7	4.0	6.0	5.1	4.3	3.8	5.0	4.2	3.7	3.2	4.0	3.5	3.0	2.7	1.8
下方投影面積			1.5	7.0	6.0	5.2	4.6	6.4	5.5	4.8	4.2	5.3	4.6	4.1	3.6	4.3	3.8	3.4	3.0	2.0
等価発光面積			2.0	7.5	6.6	5.9	5.4	6.9	6.1	5.5	5.0	5.8	5.2	4.7	4.3	4.7	4.3	3.9	3.6	2.4
取付高さ	器具間隔最大限		2.5	7.9	7.1	6.5	5.9	7.2	6.6	6.0	5.5	6.1	5.6	5.1	4.7	5.0	4.6	4.2	3.9	2.7
	横方向 (A)	縦方向 (B)	3.0	8.1	7.4	6.9	6.4	7.5	6.9	6.4	5.9	6.3	5.8	5.4	5.1	5.2	4.8	4.5	4.2	2.9
1.5m	2.39 m	1.97 m	4.0	8.5	7.9	7.4	7.0	7.8	7.3	6.9	6.5	6.6	6.2	5.9	5.6	5.5	5.2	4.9	4.7	3.3
2	3.19	2.62	5.0	8.7	8.2	7.8	7.4	8.0	7.6	7.2	6.9	6.8	6.5	6.2	5.9	5.6	5.4	5.2	4.9	3.5
2.5	3.99	3.27	7.0	8.9	8.6	8.2	7.9	8.3	8.0	7.7	7.4	7.1	6.8	6.6	6.3	5.9	5.7	5.5	5.3	3.8
3	4.79	3.92	10.0	9.1	8.9	8.6	8.3	8.5	8.3	8.0	7.8	7.3	7.1	6.9	6.7	6.1	5.9	5.8	5.6	4.1

