

屋内照明器具特性

品番 (品名)	NNN7 1 1 0 0	
光源	LED5000_70_500 ×1	500.0 1 m
管理番号	K0157863 (0) D 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	0.6	85	79	75	72	84	78	75	72	83	78	74	72	81	77	74	72	71
	中 0.63		0.8	90	85	81	78	89	84	81	78	88	83	80	78	86	83	80	78	76
	否 0.56		1.0	93	89	85	82	92	88	85	82	91	87	84	82	89	86	84	82	80
下方投影面積 等価発光面積	c m ²	c m ²	1.25	96	92	89	86	95	91	88	86	94	90	88	86	92	89	87	85	84
			1.5	98	94	92	89	97	94	91	89	95	93	90	88	94	91	89	88	86
			2.0	101	98	95	93	100	97	95	93	98	96	94	92	96	94	92	91	89
取付高さ	器具間隔最大限		2.5	102	100	98	96	101	99	97	95	99	97	96	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)	3.0	103	101	99	98	102	100	99	97	100	99	97	96	98	97	96	95	93
H m	0.37 H m	0.38 H m	4.0	105	103	101	100	104	102	101	99	102	100	99	98	100	99	98	97	94
			5.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	99	98	96
			7.0	106	105	104	104	105	104	103	103	103	102	102	101	101	100	100	99	97
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98

