

屋内照明器具特性	
品番 (品名)	XLY060ESN
光源	LED5000_85_740 x1 740.0 lm
管理番号	K0155411(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	6%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	94%																																																						
保守率	良 0.83 中 0.81 否 0.77	0.6	55	42	34	29	53	41	34	28	50	40	33	28	47	38	32	28	25																																				
		0.8	64	52	44	38	62	51	44	38	59	49	43	37	56	47	41	37	34																																				
		1.0	71	60	52	45	69	58	51	45	65	56	49	44	61	54	48	43	40																																				
		1.25	77	66	59	53	74	65	58	52	70	62	56	51	67	60	54	50	47																																				
下方投影面積	cm ²	1.5	81	71	64	58	78	70	63	57	74	67	61	56	71	64	59	55	52																																				
		2.0	86	78	72	66	84	77	71	66	80	74	68	64	76	71	66	62	59																																				
等価発光面積	cm ²	2.5	90	83	77	72	88	81	76	71	83	78	73	69	79	75	71	68	64																																				
		3.0	92	86	81	76	90	85	80	75	86	81	77	73	82	78	75	71	67																																				
取付高さ	器具間隔最大限		4.0	96	91	86	82	93	89	85	81	89	86	82	79	85	82	79	77	73																																			
	横方向 (A)	縦方向 (B)	5.0	98	93	90	86	96	92	88	85	91	88	85	83	88	85	82	80	76																																			
1.5m	1.94m	1.9m	7.0	100	97	94	91	98	95	92	90	94	92	89	87	90	88	86	84	80																																			
2	2.59	2.51	10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	91	89	88	83																																			
2.5	3.24	3.12																																																					
3	3.89	3.72																																																					

