

屋内照明器具特性

品番 (品名)	NTS75241S+NTS90551														
光源	LED4000_70_3190 x1 3190.0 lm														
管理番号	K0161312(0)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	1%	反射率	床	10%				10%				10%				10%				0%
下方光束	99%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.67	0.6	58	46	38	33	56	45	38	33	54	44	37	33	52	43	37	32	30
		0.63	0.8	68	57	50	44	67	57	49	44	64	55	49	44	62	54	48	44	41
			1.0	75	65	58	52	74	64	57	52	71	63	56	52	68	61	56	51	49
		0.56	1.25	81	72	65	60	80	71	65	60	77	69	64	59	74	68	63	58	56
下方投影面積	c m ²	1.5	85	77	71	65	84	76	70	65	80	74	69	64	78	72	67	64	61	
		2.0	90	84	78	73	89	83	77	73	86	80	76	72	83	78	74	71	69	
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	86	82	79	76	73
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	94	90	86	82	91	87	84	81	89	85	82	80	77
H m	0.92 H m	1.22 H m	4.0	99	95	91	88	97	94	90	87	94	91	88	86	92	89	87	84	82
			5.0	101	97	94	91	99	96	93	91	96	94	91	89	94	91	89	87	84
			7.0	103	100	98	96	101	99	97	95	98	96	95	93	96	94	93	91	88
			10.0	104	102	101	99	103	101	99	98	100	99	97	96	97	96	95	94	91

