

屋内照明器具特性

品番 (品名)	NTS71242S+NTS90151														
光源	LED3500_85_1140 x1 1140.0 lm														
管理番号	K0161314(0)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	1%	室指数	照明率 (X0.01)																ZCM		
下方光束	99%																				
保守率	良 中 否 0.81 0.77 0.68	0.6	59	47	40	34	58	47	39	34	55	45	39	34	53	44	38	34	32		
		0.8	70	59	51	46	68	58	51	46	65	57	50	46	63	55	50	45	43		
		1.0	76	67	60	54	75	66	59	54	72	64	58	54	69	63	57	53	51		
		1.25	82	73	67	62	81	73	66	62	78	71	65	61	75	69	64	60	58		
下方投影面積	c m ²	1.5	86	78	72	67	85	77	72	67	82	75	70	66	79	74	69	66	63		
		2.0	91	85	80	75	90	84	79	75	87	82	77	74	84	80	76	73	70		
取付高さ	器具間隔最大限		2.5	95	89	84	80	93	88	84	80	90	86	82	79	87	84	80	78	75	
	横方向 (A)	縦方向 (B)	3.0	97	92	88	84	95	91	87	83	92	89	85	82	90	86	84	81	78	
H m	0.91 H m	1.22 H m	4.0	99	96	92	89	98	94	91	88	95	92	89	87	92	90	88	86	83	
			5.0	101	98	95	92	100	97	94	92	97	94	92	90	94	92	90	89	86	
			7.0	103	101	98	96	102	99	97	95	99	97	95	94	96	95	93	92	89	
			10.0	105	103	101	100	103	102	100	99	100	99	98	97	98	97	96	95	92	

