

屋内照明器具特性	
品番 (品名)	XLX850REVC
光源	LED3500_85_4520 ×1 4520.0 lm
管理番号	K0128266 (3) DB 1
BZ分類	BZ5

器具効率 上方光束 下方光束			1 0 0 % 0 % 1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
						壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
						床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M																
保守率			良 中 否	0 . 8 1	0 . 6	5 6	4 3	3 5	3 0	5 4	4 3	3 5	3 0	5 2	4 2	3 5	3 0	5 0	4 1	3 4	3 0	2 8	
				0 . 7 7	0 . 8	6 6	5 4	4 6	4 0	6 4	5 3	4 6	4 0	6 2	5 2	4 5	4 0	5 9	5 1	4 4	4 0	3 8	
				0 . 6 8	1 . 0	7 3	6 2	5 4	4 8	7 1	6 1	5 3	4 8	6 8	5 9	5 3	4 7	6 5	5 8	5 2	4 7	4 5	
					1 . 2 5	7 9	6 9	6 1	5 6	7 7	6 8	6 1	5 5	7 4	6 6	6 0	5 5	7 1	6 4	5 9	5 4	5 2	
下方投影面積 等価発光面積			c m ²	1 . 5	8 3	7 4	6 7	6 1	8 1	7 3	6 6	6 1	7 8	7 1	6 5	6 0	7 5	6 9	6 4	6 0	5 7		
				c m ²	2 . 0	8 9	8 1	7 5	7 0	8 7	8 0	7 4	7 0	8 4	7 8	7 3	6 9	8 1	7 6	7 2	6 8	6 6	
取付 高さ	器具間隔最大限				2 . 5	9 3	8 6	8 1	7 6	9 1	8 5	8 0	7 6	8 8	8 3	7 8	7 5	8 5	8 1	7 7	7 4	7 1	
	横方向 (A)		縦方向 (B)		3 . 0	9 5	8 9	8 5	8 0	9 3	8 8	8 4	8 0	9 1	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 5	
1 . 5 m	2 . 1 3 m	2 . 8 9 m		4 . 0	9 8	9 4	9 0	8 7	9 7	9 3	8 9	8 6	9 4	9 1	8 7	8 5	9 1	8 8	8 6	8 3	8 1		
2	2 . 7 7	3 . 3 2		5 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 3	9 1	8 9	8 7	8 4		
2 . 5	3 . 4 1	3 . 8 2		7 . 0	1 0 3	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 8	9 6	9 4	9 3	9 6	9 4	9 3	9 1	8 8		
3	4 . 0 6	4 . 3 6		1 0 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 5	9 4	9 1		

