

屋内照明器具特性	
品番 (品名)	NNF 2 1 0 3 0 C
光源	LDL20S. N/ 11 / 12 - K(960) ×1 960.0 l m
管理番号	K0140079 (4) DR 1
B Z 分類	BZ6

器具効率		99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		20 % 79 %	室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.6	50	37	29	24	47	36	28	23	43	33	27	22	39	31	25	21	17	
			0.8	59	47	38	32	56	45	37	31	51	41	35	30	46	38	32	28	24	
			1.0	65	53	45	39	62	51	43	38	56	47	41	35	51	44	38	33	29	
			1.25	70	60	52	45	67	57	50	44	61	53	47	42	56	49	43	39	34	
下方投影面積 等価発光面積		cm ² cm ²	1.5	75	64	57	50	71	62	55	49	65	57	51	46	59	53	48	43	38	
			2.0	80	71	64	58	77	69	62	57	70	64	58	53	64	59	54	50	44	
取付 高さ	器具間隔最大限		2.5	84	76	70	64	80	73	67	62	73	68	63	59	67	63	58	55	48	
	横方向 (A)	縦方向 (B)	3.0	86	80	74	69	83	77	71	66	76	71	66	62	70	66	62	59	52	
1.5m	2.12 m	1.91 m	4.0	90	84	79	75	86	81	77	72	79	75	71	68	73	70	67	64	56	
2	2.83	2.51	5.0	92	87	83	79	88	84	80	76	82	78	75	72	75	72	70	67	60	
2.5	3.53	3.11	7.0	95	91	87	84	91	88	84	82	84	82	79	76	78	76	73	71	64	
3	4.25	3.72	10.0	97	94	91	89	93	91	88	86	87	84	82	80	80	78	77	75	67	

