

屋内照明器具特性	
品番 (品名)	NNF 2 2 9 1 0 J
光源	LDL20S. N/ 11 / 12 - K (9 6 0) × 2 9 6 0 . 0 l m
管理番号	K0125037 (0) DR 1
B Z 分類	BZ5

器具効率		9 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 8 1	0 . 6	5 3	4 1	3 3	2 8	5 2	4 0	3 3	2 8	4 9	3 9	3 3	2 8	4 7	3 8	3 2	2 8	2 6	
			0 . 7 7	0 . 8	6 2	5 1	4 4	3 8	6 1	5 1	4 3	3 8	5 8	4 9	4 3	3 8	5 6	4 8	4 2	3 8	3 6	
			0 . 6 8	1 . 0	6 9	5 8	5 1	4 5	6 7	5 8	5 1	4 5	6 4	5 6	5 0	4 5	6 2	5 5	4 9	4 5	4 2	
				1 . 2 5	7 5	6 5	5 8	5 3	7 3	6 4	5 8	5 3	7 0	6 3	5 7	5 2	6 7	6 1	5 6	5 2	4 9	
下方投影面積		c m ²	1 . 5	7 9	7 0	6 4	5 8	7 7	6 9	6 3	5 8	7 4	6 7	6 2	5 7	7 1	6 6	6 1	5 7	5 5		
			等価発光面積	2 . 0	8 4	7 7	7 1	6 7	8 3	7 6	7 1	6 6	8 0	7 4	7 0	6 6	7 7	7 2	6 8	6 5	6 2	
取付 高さ	器具間隔最大限		2 . 5	8 8	8 2	7 7	7 2	8 6	8 1	7 6	7 2	8 3	7 9	7 5	7 1	8 1	7 7	7 3	7 0	6 8		
	横方向 (A) 縦方向 (B)		3 . 0	9 0	8 5	8 0	7 7	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	8 3	8 0	7 7	7 4	7 2		
1 . 5 m	2 . 0 7 m	1 . 9 1 m	4 . 0	9 3	8 9	8 6	8 2	9 2	8 8	8 5	8 2	8 9	8 6	8 3	8 0	8 7	8 4	8 1	7 9	7 7		
2	2 . 7 5	2 . 5 1	5 . 0	9 5	9 2	8 9	8 6	9 4	9 1	8 8	8 5	9 1	8 8	8 6	8 4	8 9	8 6	8 4	8 2	8 0		
2 . 5	3 . 4 4	3 . 1 2	7 . 0	9 7	9 5	9 2	9 0	9 6	9 4	9 1	8 9	9 3	9 1	9 0	8 8	9 1	8 9	8 8	8 6	8 4		
3	4 . 1 4	3 . 7 3	1 0 . 0	9 9	9 7	9 5	9 4	9 8	9 6	9 4	9 3	9 5	9 4	9 2	9 1	9 3	9 2	9 1	9 0	8 7		

