

# 屋内照明器具特性

品番 (品名)	LGB16136																
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 1 m																
管理番号	K0192008 (0) DR 1																
BZ分類	BZ1																

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	85 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X0.01) ZCM																	
保守率	良	0.67	0.6	66	60	56	53	65	59	56	53	64	59	55	53	63	58	55	53	52
	中	0.63	0.8	72	67	63	60	72	66	63	60	70	66	62	60	69	65	62	60	59
	否	0.56	1.0	76	71	68	65	75	71	67	65	74	70	67	65	72	69	66	64	63
下方投影面積	c m <sup>2</sup>	1.25	79	75	72	69	78	74	71	69	77	73	71	69	75	72	70	68	67	
		1.5	81	78	75	72	80	77	74	72	79	76	73	71	77	75	73	71	69	
等価発光面積	c m <sup>2</sup>	2.0	84	81	78	76	83	80	78	76	81	79	77	75	80	78	76	74	73	
		2.5	86	83	81	79	85	82	80	78	83	81	79	78	81	80	78	77	75	
取付高さ	器具間隔最大限		3.0	87	84	82	81	86	84	82	80	84	82	81	79	82	81	79	78	77
H m	横方向 (A)	縦方向 (B)	4.0	88	86	85	83	87	85	84	83	85	84	83	82	83	82	81	80	79
	0.74 H m	0.74 H m	5.0	89	87	86	85	88	86	85	84	86	85	84	83	84	83	83	82	80
			7.0	90	89	88	87	89	88	87	86	87	86	85	85	85	84	84	83	81
			10.0	90	90	89	88	89	89	88	87	87	87	86	86	86	85	85	84	82

