

# 屋内照明器具特性

|         |                |          |  |
|---------|----------------|----------|--|
| 品番 (品名) | LGB16136       |          |  |
| 光源      | LLD2020CU1 ×1  | 468.0 lm |  |
| 管理番号    | K0191988(0)DR1 |          |  |
| BZ分類    | BZ1            |          |  |

|        |                 |         |      |     |     |     |     |     |    |    |     |     |    |    |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率   | 94%             | 天井      | 80%  |     |     |     | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 94%             | 床       |      | 10% |     |     |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 (X0.01)     |         |      |     |     |     |     |     |    |    |     |     |    |    |     |     |    |    |    | ZCM |
| 保守率    | 良 0.67          | 0.6     | 81   | 76  | 72  | 70  | 80  | 75  | 72 | 70 | 79  | 75  | 72 | 70 | 78  | 74  | 72 | 70 | 69 |     |
|        | 中 0.63          | 0.8     | 86   | 81  | 78  | 76  | 85  | 81  | 78 | 76 | 84  | 80  | 78 | 76 | 83  | 80  | 77 | 75 | 74 |     |
|        | 否 0.56          | 1.0     | 89   | 85  | 82  | 80  | 88  | 84  | 82 | 80 | 87  | 84  | 81 | 79 | 86  | 83  | 81 | 79 | 78 |     |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 92   | 88  | 85  | 83  | 91  | 87  | 85 | 83 | 89  | 86  | 84 | 82 | 88  | 85  | 83 | 82 | 81 |     |
|        |                 | 1.5     | 93   | 90  | 88  | 86  | 93  | 90  | 87 | 85 | 91  | 88  | 86 | 85 | 89  | 87  | 86 | 84 | 83 |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 96   | 93  | 91  | 89  | 95  | 92  | 90 | 89 | 93  | 91  | 89 | 88 | 91  | 90  | 88 | 87 | 85 |     |
|        |                 | 2.5     | 97   | 95  | 93  | 91  | 96  | 94  | 92 | 91 | 94  | 92  | 91 | 90 | 92  | 91  | 90 | 89 | 87 |     |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 98  | 96  | 94  | 93  | 97  | 95 | 94 | 92  | 95  | 94 | 92 | 91  | 93  | 92 | 91 | 90 | 88  |
|        | 横方向 (A)         | 縦方向 (B) | 4.0  | 99  | 97  | 96  | 95  | 98  | 97 | 95 | 94  | 96  | 95 | 94 | 93  | 94  | 93 | 93 | 92 | 90  |
| Hm     | 0.34Hm          | 0.34Hm  | 5.0  | 100 | 98  | 97  | 96  | 99  | 97 | 97 | 96  | 97  | 96 | 95 | 94  | 95  | 94 | 93 | 91 |     |
|        |                 |         | 7.0  | 100 | 99  | 99  | 98  | 99  | 99 | 98 | 97  | 97  | 97 | 96 | 96  | 95  | 95 | 95 | 94 | 92  |
|        |                 |         | 10.0 | 100 | 100 | 100 | 99  | 100 | 99 | 99 | 98  | 98  | 97 | 97 | 97  | 96  | 95 | 95 | 93 |     |

