

屋内照明器具特性	
品番 (品名)	NDNN5 7 5 1 1 K
光源	LED4000_80_5470 x1 5470.0 lm
管理番号	K0150635 (0) DB 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良	0 . 7 6	0 . 6	8 1	7 4	7 0	6 7	8 0	7 4	7 0	6 7	7 9	7 3	7 0	6 7	7 7	7 3	6 9	6 7	6 6		
		中	0 . 7 2	0 . 8	8 7	8 1	7 7	7 4	8 6	8 1	7 7	7 4	8 5	8 0	7 6	7 3	8 3	7 9	7 6	7 3	7 2		
		否	0 . 6 4	1 . 0	9 1	8 5	8 2	7 9	9 0	8 5	8 1	7 8	8 8	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 6		
				1 . 2 5	9 4	8 9	8 6	8 3	9 3	8 9	8 5	8 3	9 1	8 8	8 5	8 2	9 0	8 6	8 4	8 2	8 0		
下方投影面積		c m ²	1 . 5	9 6	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 3	9 0	8 7	8 5	9 2	8 9	8 6	8 4	8 3			
等価発光面積			c m ²	2 . 0	9 9	9 6	9 3	9 0	9 8	9 5	9 2	9 0	9 6	9 3	9 1	8 9	9 4	9 2	9 0	8 8	8 7		
				2 . 5	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 9		
取付 高さ	器具間隔最大限		3 . 0	1 0 2	1 0 0	9 7	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 3	9 1			
	横方向 (A)		縦方向 (B)		4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 3	
H m	0 . 7 8 H m		0 . 7 6 H m		5 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4	
			7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	1 0 0	9 9	9 9	9 8	9 5		
			1 0 . 0	1 0 6	1 0 5	1 0 5	1 0 4	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7			

