

屋内照明器具特性	
品番 (品名)	L G W5 1 7 0 4 B
光源	L L D 6 3 0 0 N × 1 1 2 7 0 . 0 l m
管理番号	K 0 1 6 5 6 2 3 (0) D B 1
B Z 分類	B Z 5

器具効率		6 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
						室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	3 8	2 9	2 4	2 0	3 7	2 9	2 4	2 0	3 5	2 8	2 3	2 0	3 3	2 7	2 3	2 0	1 8			
			0 . 6	0 . 8	4 4	3 6	3 1	2 7	4 3	3 6	3 0	2 7	4 1	3 4	3 0	2 6	3 9	3 3	2 9	2 6	2 4			
			0 . 5 6	1 . 0	4 9	4 1	3 6	3 2	4 7	4 0	3 5	3 2	4 5	3 9	3 5	3 1	4 3	3 8	3 4	3 1	2 9			
				1 . 2 5	5 3	4 6	4 1	3 7	5 1	4 5	4 0	3 6	4 9	4 3	3 9	3 6	4 7	4 2	3 8	3 5	3 3			
下方投影面積		c m ²	1 . 5 6	1 . 5	5 5	4 9	4 4	4 0	5 4	4 8	4 4	4 0	5 2	4 7	4 3	3 9	4 9	4 5	4 2	3 9	3 7			
等価発光面積				c m ²	2 . 0	5 9	5 4	5 0	4 6	5 8	5 3	4 9	4 5	5 5	5 1	4 8	4 5	5 3	4 9	4 6	4 4	4 2		
取付 高さ	器具間隔最大限				2 . 5	6 2	5 7	5 3	5 0	6 0	5 6	5 2	4 9	5 8	5 4	5 1	4 8	5 5	5 2	5 0	4 7	4 5		
	横方向 (A)				縦方向 (B)		3 . 0	6 3	5 9	5 6	5 3	6 2	5 8	5 5	5 2	5 9	5 6	5 3	5 1	5 7	5 4	5 2	5 0	4 8
H m	1 . 2 6 H m	1 . 2 6 H m			4 . 0	6 6	6 2	5 9	5 7	6 4	6 1	5 8	5 6	6 2	5 9	5 7	5 5	5 9	5 7	5 5	5 3	5 1		
				5 . 0	6 7	6 4	6 2	5 9	6 6	6 3	6 1	5 9	6 3	6 1	5 9	5 7	6 1	5 9	5 7	5 6	5 3			
				7 . 0	6 8	6 6	6 4	6 3	6 7	6 5	6 3	6 2	6 5	6 3	6 2	6 0	6 3	6 1	6 0	5 9	5 6			
				1 0 . 0	7 0	6 8	6 7	6 5	6 9	6 7	6 6	6 4	6 6	6 5	6 4	6 3	6 4	6 3	6 2	6 1	5 8			

