

屋内照明器具特性	
品番 (品名)	LGB15176
光源	LED2700_70_355 ×1 355.0 lm
管理番号	K0169188 (1) DR1
BZ分類	BZ1

器具効率	1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束	1 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束	8 9 %																					
保守率	良	0 . 6 3	0 . 6	7 9	7 3	6 8	6 5	7 8	7 2	6 8	6 5	7 5	7 0	6 7	6 4	7 3	6 9	6 6	6 4	6 2		
	中	0 . 6	0 . 8	8 5	7 9	7 5	7 2	8 4	7 8	7 5	7 2	8 1	7 7	7 3	7 1	7 8	7 5	7 2	7 0	6 8		
	否	0 . 5 6	1 . 0	8 9	8 4	8 0	7 7	8 8	8 3	7 9	7 7	8 4	8 1	7 8	7 5	8 2	7 8	7 6	7 4	7 1		
			1 . 2 5	9 3	8 8	8 4	8 2	9 1	8 7	8 3	8 1	8 7	8 4	8 1	7 9	8 4	8 1	7 9	7 7	7 5		
下方投影面積	c m ²		1 . 5	9 5	9 1	8 7	8 5	9 3	8 9	8 6	8 4	8 9	8 6	8 4	8 2	8 6	8 4	8 2	8 0	7 7		
等価発光面積	c m ²		2 . 0	9 8	9 4	9 1	8 9	9 5	9 2	9 0	8 8	9 2	8 9	8 7	8 5	8 8	8 6	8 5	8 3	7 9		
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 4	9 2	9 7	9 4	9 2	9 0	9 3	9 1	8 9	8 8	8 9	8 8	8 6	8 5	8 1		
	横方向 (A)	縦方向 (B)	3 . 0	1 0 0	9 8	9 5	9 4	9 8	9 6	9 4	9 2	9 4	9 2	9 1	8 9	9 0	8 9	8 8	8 7	8 2		
H m	0 . 4 9 H m	0 . 4 9 H m	4 . 0	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 5	9 5	9 4	9 3	9 1	9 1	9 0	8 9	8 8	8 4		
			5 . 0	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 6	9 5	9 4	9 3	9 2	9 1	9 0	9 0	8 5		
			7 . 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 7	9 6	9 5	9 4	9 3	9 2	9 2	9 1	8 6		
			1 0 . 0	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 8	9 7	9 6	9 6	9 3	9 3	9 2	9 2	8 7		

