

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 6 1
光源	LDA3 L - E17 / C / W ×1 280.0 l m
管理番号	K0169956 (1) DR 1
B Z 分類	BZ5 / 0.7 / BZ4 / 6.0 / BZ5

器具効率		47 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01)																			
保守率		良 中 否	0.67	0.6	27	21	18	15	26	21	17	15	24	20	17	15	23	19	16	14	13					
			0.63	0.8	31	26	23	20	30	26	22	20	29	25	22	19	27	24	21	19	18					
			1.0	1.0	34	30	26	24	33	29	26	24	32	28	25	23	30	27	24	22	21					
			0.56	1.25	37	33	30	27	36	32	29	27	34	31	28	26	32	30	27	26	24					
下方投影面積		c m ²	1.5	39	35	32	30	38	35	32	30	36	33	31	29	34	32	30	28	26						
			2.0	42	38	36	34	40	38	35	33	38	36	34	32	36	34	33	31	29						
等価発光面積		c m ²	2.5 <td>43</td> <td>40</td> <td>38</td> <td>36</td> <td>42</td> <td>39</td> <td>37</td> <td>36</td> <td>40</td> <td>38</td> <td>36</td> <td>34</td> <td>38</td> <td>36</td> <td>35</td> <td>33</td> <td>31</td> <td></td> <td></td>	43	40	38	36	42	39	37	36	40	38	36	34	38	36	35	33	31						
			3.0	44	42	40	38	43	41	39	37	41	39	37	36	39	37	36	35	33						
H m	0.76 H m		0.78 H m	4.0	45	43	42	40	44	43	41	40	42	41	39	38	40	39	38	37	35					
				5.0	46	45	43	42	45	44	42	41	43	42	41	40	41	40	39	38	36					
				7.0	47	46	45	44	46	45	44	43	44	43	42	41	42	41	40	40	37					
				10.0	48	47	46	45	47	46	45	44	45	44	43	43	43	42	42	41	39					

