

屋内照明器具特性	
品番 (品名)	L G B 1 1 0 8 4
光源	LED2700_70_398 ×1 398.0 l m
管理番号	K0164288 (0) DB 1
B Z 分類	BZ3 / 1.8 / BZ4 / 8.5 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 2 % 8 8 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	6 1	5 0	4 4	3 9	5 9	4 9	4 3	3 8	5 6	4 8	4 2	3 8	5 3	4 6	4 1	3 7	3 4				
			0 . 6 3	0 . 8	7 0	6 1	5 4	4 9	6 8	5 9	5 3	4 8	6 5	5 7	5 1	4 7	6 1	5 5	5 0	4 6	4 3				
			1 . 0	7 6	6 7	6 1	5 6	7 4	6 6	6 0	5 5	7 0	6 3	5 8	5 4	6 6	6 0	5 6	5 2	4 9					
			0 . 5 6	1 . 2 5	8 1	7 3	6 7	6 2	7 9	7 2	6 6	6 1	7 5	6 8	6 3	6 0	7 1	6 5	6 1	5 8	5 4				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 5	7 7	7 1	6 7	8 2	7 6	7 0	6 6	7 8	7 2	6 8	6 4	7 4	6 9	6 5	6 2	5 8					
			2 . 0	8 9	8 3	7 8	7 4	8 7	8 1	7 6	7 2	8 2	7 7	7 3	7 0	7 8	7 4	7 0	6 8	6 3					
取付 高さ	器具間隔最大限		2 . 5	9 2	8 7	8 2	7 8	9 0	8 5	8 0	7 7	8 5	8 1	7 7	7 4	8 0	7 7	7 4	7 1	6 7					
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 9	8 5	8 2	9 2	8 7	8 3	8 0	8 7	8 3	8 0	7 7	8 2	7 9	7 7	7 4	6 9					
H m	1 . 2 4 H m	1 . 2 4 H m	4 . 0	9 7	9 3	8 9	8 6	9 4	9 1	8 8	8 5	8 9	8 6	8 4	8 1	8 5	8 2	8 0	7 8	7 3					
			5 . 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 1	8 8	8 6	8 4	8 6	8 4	8 2	8 1	7 5					
			7 . 0	1 0 0	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 3	9 1	8 9	8 8	8 8	8 7	8 5	8 4	7 8					
			1 0 . 0	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 4	9 4	9 3	9 2	9 0	9 0	8 9	8 7	8 6	8 0					

