

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 5
光源	L L D 4 0 0 0 L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 4 1 9 (0) D R 1
B Z 分類	B Z 9 / 0 . 9 / B Z 8

器具効率		81 % 上方光束 41 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
		40 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	36	26	19	15	33	24	18	14	27	20	15	11	21	16	12	9	5
			0.6	0.8	43	33	26	21	39	30	24	19	32	25	20	16	25	20	16	13	8
			0.56	1.0	47	38	31	26	43	35	29	24	35	29	24	20	28	23	19	16	10
				1.25	52	43	36	31	47	40	33	29	39	33	28	24	31	27	23	20	12
下方投影面積 等価発光面積		cm ²		1.5	55	47	40	35	51	43	37	33	42	36	31	27	33	29	25	22	14
				2.0	60	52	47	42	55	48	43	39	45	40	36	33	37	33	30	27	17
取付 高さ	器具間隔最大限			2.5	63	56	51	46	58	52	47	43	48	44	40	36	39	36	33	30	20
	横方向 (A) 縦方向 (B)			3.0	65	59	54	50	60	55	50	46	50	46	42	39	41	38	35	32	22
H _m	1.59 H _m	2.09 H _m		4.0	68	63	59	55	63	58	54	51	52	49	46	43	43	40	38	36	25
				5.0	70	65	62	58	64	61	57	54	54	51	49	46	45	42	40	38	27
				7.0	72	69	66	63	66	64	61	58	56	54	52	50	47	45	43	42	29
				10.0	74	71	69	67	68	66	64	62	58	56	55	53	48	47	46	44	31

