

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 6
光源	LLD2000LCB1 ×1 531.0 lm
管理番号	K0175300 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		4 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束 下方光束		2 0 % 2 1 %	室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	2 1	1 6	1 3	1 1	1 9	1 5	1 2	1 0	1 6	1 3	1 1	9	1 3	1 1	9	8	6
			0 . 6	0 . 8	2 4	2 0	1 7	1 5	2 3	1 9	1 6	1 4	1 9	1 6	1 4	1 3	1 6	1 4	1 2	1 1	8			
			0 . 5 6	1 . 0	2 7	2 3	2 0	1 8	2 5	2 2	1 9	1 7	2 1	1 9	1 7	1 5	1 8	1 6	1 4	1 3	1 0			
			1 . 2 5	2 9	2 6	2 3	2 1	2 7	2 4	2 2	2 0	2 3	2 1	1 9	1 7	1 9	1 8	1 6	1 5	1 2				
下方投影面積		c m ²	1 . 5	3 1	2 8	2 5	2 3	2 9	2 6	2 4	2 2	2 5	2 2	2 1	1 9	2 1	1 9	1 8	1 7	1 3				
等価発光面積			c m ²	2 . 0	3 3	3 0	2 8	2 6	3 1	2 8	2 6	2 5	2 6	2 5	2 3	2 2	2 2	2 1	2 0	1 9	1 4			
				2 . 5	3 4	3 2	3 0	2 9	3 2	3 0	2 8	2 7	2 7	2 6	2 5	2 3	2 3	2 2	2 1	2 0	1 5			
取付 高さ	器具間隔最大限		3 . 0	3 5	3 3	3 2	3 0	3 3	3 1	3 0	2 8	2 8	2 7	2 6	2 5	2 4	2 3	2 2	2 1	1 6				
H m	0 . 0 0 H m	1 . 6 7 H m	4 . 0	3 7	3 5	3 4	3 2	3 4	3 3	3 1	3 0	2 9	2 8	2 7	2 6	2 5	2 4	2 3	2 3	1 7				
			5 . 0	3 7	3 6	3 5	3 4	3 5	3 4	3 3	3 2	3 0	2 9	2 8	2 7	2 5	2 5	2 4	2 4	1 8				
			7 . 0	3 8	3 7	3 6	3 5	3 6	3 5	3 4	3 3	3 1	3 0	2 9	2 9	2 6	2 5	2 5	2 5	1 8				
			1 0 . 0	3 9	3 8	3 7	3 7	3 6	3 5	3 5	3 4	3 1	3 1	3 0	3 0	2 6	2 6	2 6	2 5	1 9				

