

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 0 6
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178754 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		37 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		18 %	室指数	照明率 (X0.01)																		Z CM
下方光束		19 %																				
保守率		良 中 否	0.63	0.6	18	14	12	10	17	13	11	9	14	12	10	8	12	10	8	7	5	
			0.6	0.8	22	18	15	13	20	17	14	13	17	15	13	11	14	12	11	10	7	
			0.56	1.0	24	21	18	16	22	19	17	15	19	17	15	13	16	14	13	12	9	
				1.25	26	23	21	19	24	22	19	18	21	19	17	16	17	16	15	14	10	
下方投影面積		cm ²		1.5	28	25	22	21	26	23	21	19	22	20	18	17	18	17	16	15	11	
等価発光面積			cm ²	2.0	30	27	25	24	28	25	24	22	24	22	21	19	20	19	18	17	13	
取付 高さ	器具間隔最大限			2.5	31	29	27	25	29	27	25	24	25	23	22	21	21	20	19	18	14	
	横方向 (A)		縦方向 (B)	3.0	32	30	28	27	29	28	26	25	25	24	23	22	21	20	20	19	14	
H m	0.00 H m	1.67 H m		4.0	33	31	30	29	30	29	28	27	26	25	24	24	22	21	21	20	15	
				5.0	33	32	31	30	31	30	29	28	27	26	25	25	23	22	22	21	16	
				7.0	34	33	32	32	32	31	30	30	27	27	26	26	23	23	22	22	16	
				10.0	35	34	33	33	32	32	31	31	28	27	27	27	24	23	23	23	17	

