

屋内照明器具特性

品番 (品名)	LGB12625				
光源	LED6200_70_3405 x1 3405.0 lm				
管理番号	K0158852(0)D 1				
BZ分類	BZ5/0.7/BZ4				

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
		床	10%				10%				10%				10%				0%		
上方光束	8%	室指数																			
下方光束	92%	照明率 (X0.01) ZCM																			
保守率	良	0.67	0.6	57	45	38	32	55	44	37	32	52	43	36	32	49	41	35	31	29	
	中	0.63	0.8	67	56	49	43	65	55	48	43	62	53	47	42	58	51	45	41	38	
	否	0.56	1.0	74	64	56	51	72	62	56	50	68	60	54	49	64	58	53	48	45	
			1.25	80	71	64	59	78	69	63	58	74	67	61	57	70	64	59	55	52	
下方投影面積			1.5	84	76	69	64	82	74	68	63	77	71	66	62	74	68	64	60	57	
			2.0	89	82	77	72	87	81	76	71	83	78	73	69	79	75	71	68	64	
等価発光面積			2.5	92	87	82	78	90	85	80	77	86	82	78	74	82	78	75	72	68	
	取付高さ	器具間隔最大限		3.0	95	90	85	82	93	88	84	80	88	84	81	78	84	81	78	76	72
		横方向 (A)	縦方向 (B)	4.0	98	94	90	87	95	92	88	86	91	88	85	83	87	85	83	80	76
1.5m	1.93m	1.93m		5.0	99	96	93	90	97	94	91	89	93	90	88	86	89	87	85	83	79
2	2.55	2.55		7.0	101	99	96	94	99	97	95	93	95	93	91	90	91	90	88	87	82
2.5	3.15	3.15		10.0	103	101	99	98	101	99	97	96	97	95	94	93	93	92	91	90	85
3	3.78	3.78																			

